

3 AAA BATTERIES

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

XPP-5454GC

NIGHTSTICK®


Life Depends on Light™



Dual-Light™ spotlight and floodlight at the same time





Integrated Stainless Steel Clip attaches to hard hat mounting bracket (included)



IP-X7 waterproof, impact & chemical resistant



Dual switches located on top of light



160 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

3 AAA BATTERIES

ITEM NUMBER/UPC

- XPP-5454GC, UPC 0 17398 80450 9

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, INMETRO

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 115L, 5 hrs. runtime
- LOW: 60L, 16.25 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH: 120L, 5.25 hrs. runtime
- LOW: 60L, 16.75 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- HIGH: 160L, 3.5 hrs. runtime

CANDELA

- HIGH: 1,668
- LOW: 882

BEAM DISTANCE

- HIGH: 82m
- LOW: 60m

DUST/WATER RATING

ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.1 in (53 mm)
- WIDTH: 2.6 in (66 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.3 oz (97 g)

BATTERY







- AAA

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp with hard hat clip
- Hard hat mount
- Self-stick PSA
- 3 AAA batteries

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	115 LUMENS	60 LUMENS	160 LUMENS
	5h	16h	3h 30min
	82m		
	1668cd		
			
			

Bayco Products, Inc. XPP-5454G
640 S. Sanden Blvd., Wylie, TX 75098



ID 4008947
INTRINSICALLY SAFE
SECURITE INTRINSEQUE



Intertek

CLASS I DIV 1 GRPS A-D T3
CLASS II & III GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T3 Ga

Ex ia IIC T3 Ga
© II 1 G Ex ia op is IIC T3 Ga

CE 0359

Conforms to:
ANSI/UL STD 913, ANSI/UL
60079-0, ANSI/UL 60079-11

Ex ia op is IIC T3 Ga
Intertek ITS 13 ATEX27928X
IECEx ITS 18.0030X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell E92 or EN92

Certified to:
CAN/CSA STD C22.2 No 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

CERTIFIED

