
SABRE® DUAL PROPELLANT SYSTEM (DPS) SERIES

Aerosol Grenade Technical Specifications

| MK 3 Grenade | | | | |
|-------------------|---------------------------------|--|--|--|
| Height: | 3.75" / 9.5 cm | | | |
| Diameter: | 1.50" / 3.80 cm | | | |
| Weight: | 2.0 oz. / 56 gr. / 60 ml | | | |
| Warranty: | 5 years | | | |
| Time to Empty: | 6 seconds | | | |
| Firing Mechanism: | Locking actuator | | | |
| Propellant: | HFC 134a | | | |
| Canister: | Seamless extruded aluminum - 2Q | | | |
| Operating Temps: | 0° F (-17° C) to 120° F (50° C) | | | |
| | | | | |



| MK 5 Grenade | | | | |
|-------------------|---------------------------------|--|--|--|
| Height: | 5.25" / 13.3 cm | | | |
| Diameter: | 2.13" / 5.5 cm | | | |
| Weight: | 5.0 oz. / 140 gr. / 150 ml | | | |
| Warranty: | 5 years | | | |
| Time to Empty: | 14 seconds | | | |
| Firing Mechanism: | Locking actuator | | | |
| Propellant: | HFC 134a | | | |
| Canister: | Three piece tin -2Q | | | |
| Operating Temps: | 0° F (-17° C) to 120° F (50° C) | | | |
| | | | | |

Formulation: Oil soluble Oleoresin Capsicum combined with an ultraviolet marking dye. The formulation is non-flammable and electronic immobilization device compatible. Each canister is stabilized and contains an operating pressure of 100 PSI. The pharmaceutical grade propellant is non-ozone depleting, providing greater dependability and a much-improved shelf life.

Labeling: All canisters are labeled with a protective Mylar over lamination cover which resists wear and water damage. Canisters are labeled with the shot pattern, batch number, serial number and expiration date. Individually serialized canisters permit easy identification and link to formulation batch numbers for quality assurance tracking.

Quality Control: Manufacturer maintains quality control system in accordance with the American National Standards Institute (ANSI) for the following:

Operation Test Discharge Duration Test Intermittent Discharge Test High Temperature Exposure Test

Temperature Cycle Test Operating Weight Test Gasket Dependability Test Hydrostatic Pressure Test

One Year Time Leakage Test Pressure Vessel Test

1/2011

Federal Regulations: The manufacturer certifies that all units comply with the following:

29 CFR 1910 Occupational Safety And Health Standards AOAC 995.03 Oleoresin Capsicum Assay

16 CFR 1500.41 Test for skin irritant 16 CFR 1500.130 Labeling of self pressurized canisters

16 CFR 1500.45 Test method for determining flammability 16 CFR 1500.42 Test for eye irritant

of contents of self pressurized canisters 16 CFR 1500.3 Acute Inhalation Toxicity Study

| | Tra | ining | Level III Formula | |
|------------------|--------------------------|-----------|------------------------|-----------|
| | SABRE [®] Inert | | SABRE Red [®] | |
| Model # | 20H2O10-G | 20H2040-G | AG-10 | AG-40 |
| Delivery | Grenade | Grenade | Grenade | Grenade |
| Range (Ft/Mtrs) | 10' X 10' | 20' X 20' | 10' X 10' | 20' X 20' |
| Active Ingred | NA | | 10% OC | |
| SHU's | NA | | 2,000,000 | |
| Scoville Content | N | NA . | 200,000 | |
| Capsaicinoids | N | ۱A | 1.33%* | |

^{*} AOAC Official Method 995.03 Capsaicinoids in Capsicums and Their Extractives, Liquid Chromatographic Method (HPLC). Security Equipment Corporation uses AOAC Method 995.03 because it is the preferred method of the Environmental Protection Agency and the U.S. Federal Government.

Last Update:

^{*} size equivalent to First Defense® MK-3; 10% PepperFoam® MK-3;

^{5.5%} PepperMace® MK-3; Pepper 10® MK-3