Hand Plus® +

TECHNICAL DATA SHEET



Features

Safety Sealed Packaging (S-XL) 100 Gloves/Box, 10 Boxes/Case

- · Powder-free; Premium Latex Gloves
- Natural Color
- 5 mil finger thickness
- Comfortable, silky textured finish
- Perfect for janitorial, electronic assembly, manufacturing and aeronautics
- Ambidextrous
- Dated Lot Codes for quality assurance and traceability

HandPlus® Latex Manufacturing Standards

*Brand new state-of-the-art manufacturing plant with computercontrolled market leading technology

Inspection Level	AQL
G1	2.5
G1	2.5
G1	4.0
S-2	4.0
	G1 G1

HandPlus® Latex Exam Powder-Free Gloves

Size	Reorder#
Small	061-6
Medium	061-7
Large	061-8
X-Large	061-9

All specifications are subject to change without notice.

Specification

Size	Glove Length	Palm Width	Cuff Thickness	Palm Thickness	Finger Thickness
Small	240	75	0.09 ± 0.01	0.10±0.01	0.13 ± 0.01
Medium	240	85	0.09 ± 0.01	0.10 ± 0.01	0.13 ± 0.01
Large	240	95	0.09 ± 0.01	0.10±0.01	0.13 ± 0.01
X-Large	240	105	0.09 ± 0.01	0.10±0.01	0.13 ± 0.01

Quality Standards

Testing Methods

- Meets or exceeds the following standards: ASTM D3578, D5712, EN 455 (1&2), AS 40 (Australia), FDA, CE
- Quality sampled in accordance with MIL STD 105D
- ISO 9001 Certified Manufacturing

Physical Properties

Property	ASTM Minimum	HandPlus® Latex
	Before Aging	Before Aging
Tensile (MPa)	18	18
Elongation (%)	650	650

	After Aging After Aging	After Aging After Aging
Tensile (MPa)	14	14
Elongation (%)	600	600