

British Safety Industry Federation, BSIF House, 3 Austins Mews, Hemel Hempstead, Hertfordshire, HP1 3AF

Reference

For the attention of Mr F. Angear

9-10-2015

Dear Sir

VALIDATION OF FIT TEST METHODS

There have recently been queries about the status of fit tests and whether fit checks can be used in place of a fit test.

HSE considers the qualitative and quantitative fit test methods described in OC 282/28 to be suitable and sufficient. Any other method used would need to be supported with validated evidence that demonstrates its suitability as a fit test. At the moment we do not consider any alternative fit test methods to be suitable.

If a HSE Inspector is presented with an alternative, un-validated fit test method on site then they will take the appropriate enforcement action.

HSE are keen to continue working with industry to refine existing methods and investigate and develop additional methods.

Yours faithfully

Dr Peter Griffin

Principal Specialist Inspector

Poter buthin

Occupational Hygiene/Noise and Vibration

Field Operations Directorate

Dr Peter Griffin

Occupational Hygiene/Noise and Vibration Unit Specialist Group Redgrave Court Merton Road Bootle Merseyside L20 7HS

Tel: 0151 951 4808 Fax: 0151 951 3131 Peter.Griffin@hse.gsi.gov.uk

http://www.hse.gov.uk/

Head of Occupational
Hygiene/Noise and Vibration Unit
Dr Christine Snaith