



SERIES
REMOTE-OPERATED
ROBOTIC MOWERS



REMOTE-OPERATED ROBOTIC MOWERS THAT CREATE OPPORTUNITIES

R SERIES MOWERS FOR MAINTAINING STEEP SLOPES & EXTREME LANDSCAPES

IDEAL FOR:

- Hillside & steep-incline maintenance
- Wetland & swamp preservation
- Dam & levee embankments
- Landfill slope preservation
- Retention or water treatment ponds
- Roadside mowing



R-60



R-52



SERIES
 REMOTE-OPERATED
 ROBOTIC MOWERS



COMPARISON CHART



ENGINE	Kawasaki® FX1000V EFI	Kawasaki® FX850V
HORSEPOWER	38.5	27
DISPLACEMENT	999 cc	852 cc
DRIVE SYSTEM	Hydro-Gear® ZT-4400 Transaxles	Hydro-Gear® ZT-4400 Transaxles
FUEL CAPACITY	13.4 Gallons	13.4 Gallons
GROUND SPEED	6.7 mph (Transport) / 5.7 mph (Mowing)	6.7 mph (Transport) / 5.7 mph (Mowing)
CUTTING WIDTH	60 Inches	52 Inches
ACRES PER HOUR	3.1	2.7
SLOPE CLIMB ABILITY	50 Degrees	50 Degrees
DECK CONSTRUCTION	3/8" Thick Deck Across Spindles	3/8" Thick Deck Across Spindles
DECK ENGAGEMENT	Ogura® Soft Start Electric Clutch	Ogura® Soft Start Electric Clutch
CUTTING HEIGHTS	2.5 - 7 Inches	2.5 - 7 Inches
TRACK CONSTRUCTION	Rubber Molded Over Steel Links	Rubber Molded Over Steel Links
TRACK SIZE / STYLE	9 Inches / Tread Style 'J'	9 Inches / Tread Style 'J'
WEIGHT	1,900 Pounds	1,850 Pounds
LENGTH	90 Inches	90 Inches
WIDTH	82 Inches	74 Inches
HEIGHT	49.5 Inches	49.5 Inches
WARRANTY	2 Years / 400 Hours	2 Years / 400 Hours