

9" x 138" Oscillating Edge Sander



SB1117



South Bend® 9" x 138" Oscillating Edge Sander

SB1117

FEATURES

- Miter work stop
- Quick-release belt lever
- Conveniently located belt tracking and tension adjustment
- ¼" belt oscillation
- Two large sanding tables
- End guards swing away for edge sanding long boards
- Table height handwheel for easy and precise adjustment and maximum use of sanding surface area
- US based customer service and technical support

SPECIFICATIONS

- Motor: 3 HP, 220V, single-phase, 15A
- Sanding belt size: 9" x 138½"
- Sanding belt speed: 4120 FPM
- Oscillations: ¼"
- Platen size & type: 9½" x 47½", graphite-coated
- Main table size: 11¾" W x 47¾" L x 1¼" T
- Main table tilt: 0–45°
- Main table vertical travel: 8"
- Auxiliary table size: 13" W x 18" L x 1¼" T
- Auxiliary table vertical travel: 8"
- Number of dust ports: 2
- Dust port size: 4"
- Footprint: 24½" x 42"
- Overall dimensions: 82" W x 24" D x 45½" H
- Approximate shipping weight: 873 lbs.

WHEN IT'S TIME TO INVEST IN YOUR SHOP'S FUTURE WITH A NEW EDGE SANDER, THIS IS THE CHOICE FOR PROFESSIONALS.

AN INDUSTRIAL-DUTY EDGE SANDER FOR HIGH-OUTPUT PROFESSIONAL SHOPS

When producing flawless work all day every day is a basic requirement of your shop, you need to trust your machinery to perform at the highest level, to be versatile to meet varying demands, and be consistently reliable to last years of rigorous use.

The 9" x 138½" Oscillating Edge Sander is a large-capacity oscillating edge sander designed for the rigors of industrial-level use.

Featuring a heavy-duty precision-ground cast-iron table that spans the length of the sanding belt, this industrial-duty oscillating edge sander from South Bend has the capacity and power your shop needs.

A 3HP motor drives the 9" x 138½" belt at 4120 FPM, with smooth ¼" oscillations, improving finish and prolonging belt life.

It also features an auxiliary contour sanding table with 8" of vertical travel mounted to the side of the machine.

Sanding belt changes are fast and easy with the quick-release belt tension lever and roller adjustment features, allowing you more time to focus on creating your best work.

BUILT TO TRUE SOUTH BEND HIGH-PRECISION INDUSTRIAL STANDARDS

The manual was written by our U.S. based Technical Documentation Department and is packed with useful information. The complete and easy to read manual provides full instructions on how to assemble and maintain your bandsaw.

The South Bend Customer Service and Technical Support Teams are U.S. based. Parts and accessories for the bandsaw are available on-line and shipped from the South Bend parts warehouse in Springfield, MO.

WARRANTY INFORMATION

South Bend Tool Company warrants every product it sells for a period of 2 years to the original purchaser from the date of purchase. We make every effort to ensure that our products meet high quality and durability standards so that you never need to use the warranty. Please feel free to write or call us if you have any questions about the machine or the manual.

for more information visit www.southbendtools.com/pages/warranty

Another view of the Oscillating Edge Sander with the heavy-duty precision-ground cast-iron table tilted at 45 degrees.



Because quality and precision are timeless.

www.southbendtools.com
sales@southbendtools.com
(360) 734-1540