

Atlas Copco



Your site. Your light

The HiLight range of light towers

We have the light tower to suit any needs

The HiLight range of light towers were designed to offer the widest choice when it comes to finding the light tower that is right for your application. We provide multiple range of industries with a flexible and dynamic set of lighting options, while addressing all aspects of efficiency and safety. You can also be assured of the robust build quality and compact size for which Atlas Copco is globally recognized.

We have really put our innovation stamp on LED technology. The lenses in our LED light towers have a very special optic designed specifically for construction and mining applications.

This innovative, fully directional, LED lens design means we maximize the light coverage and reduce "lighting waste". A single HiLight tower can cover an area of up to 6.000 m² with a 20 lux (brightness) average – ensuring a brighter, safer and more productive site.

On top of that, we have a strong commitment with the innovation and the environment, and therefore we have developed new technologies that provide bright and efficient light with zero emissions, zero fuel consumption and even zero noise. Just take a look.



Building a brighter future with solar energy

HiLight S2+ uses solar radiation as an energy source, providing silent and cleaner operations in construction projects, mining, oil and gas, and event sites.





HiLight S2+

Solar-powered light tower



The new user-friendly solar-powered LED light tower, HiLight S2+, delivers efficient, high performance, giving workers good visibility, while allowing sites to increase their sustainability and comply with zero CO2 emission and noise regulations.

The HiLight S2+ delivers 2.000 m2 light coverage and can be easily manoeuvred into place and solar panels set up; they are simply pulled out from the canopy and can be adjusted to best align with the sun's position.

The HiLight S2+ features an external control panel, and dimming function to increase autonomy efficiency.

The new solar light tower provides autonomous operation. In cases where energy demand is higher than solar yield, the light tower can also be charged with any external power grid. Batteries can be recharged with solar energy in 8 hours or an external power source in just 3 hours.

This light tower offers a robust alternative for end users and rental companies operating in construction projects, mining, oil and gas and event sites. Since the tower works at temperatures from -5°C to +50°C and can operate reliably at high altitude without derating, it is also ideal for remote work sites.



LED Light

Pop-up canopy and extensible solar panels

ZERO NOISE
EMISSIONS
FUEL CONSUMPTION

<p>UP TO 6 TON CO₂ REDUCTION*</p>	<p>UP TO 11 HOURS AUTONOMY AT 100%</p>	<p>LIFE SPAN 50.000 Hrs LED</p>
<p>MINIMUM MAINTENANCE TIME AND COST</p>	<p>DIMMABLE LED 4X90W</p>	<p>LIGHT COVERAGE 2.000 m²</p>

(* compare to diesel light towers)

HiLight B6+

The smart light tower

The ultra-quiet LED light tower HiLight B6+ has been designed to be seen and not heard while ensuring maximum safety at the site.

Delivering operating noise levels as low as 55 dBA, the renewed version of the HiLight B6+ light tower is ideally suited to provide illumination at events, temporary public lighting or enhanced visibility at construction sites located near residential areas.

The HiLight B6+ can be equipped with a new innovation called the **SmartMast™(*)**, which automatically lowers itself when safety or stability is compromised. The proprietary vertical mast technology from Atlas Copco features in-built sensors that detect when safety or stability of the light tower is compromised due to critical environmental or sites conditions, and alerts end users to potential obstacles and impacts. It also provides stability assistance when installing a light tower, for instance by flagging up irregular surfaces and floors, to ensure safe siting.



SMART MAST

LIFE SPAN
50.000 Hrs

LIGHT COVERAGE
6.000 m²

SERVICE INTERVAL (HRS)
600

TRANSPORT EFFICIENCY
22 ut 13m Truck

55 dB(A) at 7 m

START PHOTOCELL

WEEKLY TIMER

(*) Check availability

HiLight H6+

More than meets the eye

This new light tower offers low operational costs and reduced noise levels while increasing illumination coverage. It is ideal to use in tough environments, such as applications in construction, mining, and rental companies.

The HiLight H6+ comes with the innovative **HardHat® body**, made of medium-density polyethylene rather than metal, to protect the working operation underneath from the elements. The HardHat® is **resistant to corrosion**, lightweight, crack-resistant, environmentally friendly, and better able to meet the tough demands of on-site use.

It features a new generation of LED floodlights that are more efficient and provide optimal light distribution up to **6.000 m² illumination area** with a life expectancy of 50.000 hours. To offer the right luminosity at each moment and increased autonomy, the new HiLight H6+ comes with a dimming function on the easy-to-use control panel, located in an exterior lateral of the light tower.

Maintenance and transport efficiency were a priority when designing the HiLight H6+. On the first front, the light tower only requires a **simple service** after 600 hours of operation which can be carried out in 40 minutes.




New

LED Light


The new **HiLight H6+** comes with three different ways of transporting; the integrated lifting point, four forklift slots and three different tow bars to choose. The adjustable tow bar provides **flexibility**, as it allows users to handle and transport the HiLight H6+ easily while towing with vans, trucks, and pick-ups.



Forklift slots



Integrated lifting point



Straight / Foldable / Adjustable tow bar



One side service



HardHat® BODY

UP TO **40% LESS FUEL AND CO₂ EMISSIONS***

-5dB(A) LOWER NOISE

40Min EVERY 600Hrs

LIGHT COVERAGE 6.000 m²

LIFE SPAN 50.000 Hrs

*with dimming function



HiLight V4+ and HiLight V5+

The HiLight V4+ and the HiLight V5+ include a HardHat® canopy as standard, which ensures maximum protection of internal parts. This range of light towers is perfect for multiple drop rental applications and providing users a **robust and easy-to-transport set of lighting options that match any site requirements**. Thanks to its compact dimensions, 16 units can be loaded on a 13-metre truck. The extended safety features also guarantee the protection of bulbs during transportation.



LED Light
4X250W



LED Light
4X350W

LIGHT
COVERAGE
4.000 m²

300
HOURS
RUNTIME
(110 L FUEL TANK)

0,36 l/h

SERVICE
INTERVAL (HRS)
600

63 dB(A)
at 7 m

LIGHT
COVERAGE
5.000 m²

Spillage free
frame

0,7 l/h

(*) Available in 50 and 60Hz Tier4 final. Trailer comply with DOT US regulations. For EU Trailer please contact Atlas Copco representative.



HiLight V4 and V4W

The HiLight V4 offers increased serviceability with wide wing doors and all components easily accessible. Environmental considerations have also been taken into account, with a frame design that prevents oil, fluids and fuel from leaking out and contaminating the ground.


The HiLight V4W offers the best performance at **high altitudes and in the most extreme environments - thanks to its 8kW engine**. In addition, the larger fuel tank and low fuel consumption allow longer run times between refueling. The HardHat® canopy ensures maximum protection of internal parts.



TRANSPORT EFFICIENCY
16 ut 
↳ 13m Truck

 **2 l/h**

LIGHT COVERAGE
4.000 m²

METAL HALIDE
LIFE SPAN
6.000 Hrs 

HardHat® technology 
 Spillage free frame 

 **90 HOURS RUNTIME**

 **OPERATION IN EXTREME ENVIROMENTS**

 **1,7 l/h**



UP TO
15%
BRIGHTER




HiLight E3+

Electric light tower with HardHat®

The renew HiLight E3+, will operate reliably throughout the most demanding conditions found at construction sites, outdoor events and temporary public lighting installations. Its internal electronics, control panel and connectors are protected from the elements by the company's innovative HardHat® canopy, while the complete assembly, which includes a heavy-duty 7 metre mast, has a certified wind stability of 100 km/h. **Easy to plug into any power source including auxiliary power, electrical generator or directly into the grid.**

With no mechanical parts to maintain, and no liquids or emissions, the light tower is environmentally friendly and virtually maintenance-free.



E-LED

<p>Exclusive HardHat® technology</p>	<p>TRANSPORT EFFICIENCY 32 ut <small>← 13m Truck</small></p>	<p>7m 100km/h WIND STABILITY </p>	
<p>LIFE SPAN 50.000 Hrs </p>	<p>LIGHT COVERAGE 3.000 m² </p>	<p>PLUG & LIGHT </p>	<p>ZERO FUEL AND CO₂ EMISSIONS </p>



HiLight V2+

HiLight V3+

These electric plug & light solutions provide flexible lighting options for a wide range of applications. The HiLight V2+ and V3+ come with a robust steel frame with PE bumpers.

These bumpers are designed to the same standards as the HardHat® Canopy.



E-LED



E-LED



EASY TO TRANSPORT

LIGHT COVERAGE
 2.000 m² v2+
 3.000 m² v3+

LIFE SPAN

50.000
Hrs

(*) CE models, please consult



HiLight P2+

Supplied with a special lighting optic, covered by an integrated polyethylene housing, you can be assured of no burn out and a longer lifetime. In addition, great performance comes from the unique floodlight that spreads **light 360 degrees, giving users a larger illuminated area compared to traditional balloon style towers.**



PLUG & LIGHT 	 50km/h WIND STABILITY
LIGHT COVERAGE 2.000 m² 	ZERO FUEL AND CO ₂ EMISSIONS
 NO AIR PRESSURE NEED	 ANTIBURNT FLOODLIGHT



No access to the grid?

Suggested power sources; iP and P generators

	P2000 i	P3500 i	P3000	P6500	P8000
	1,6 kW	3 kW	2,3 kW	5 kW	6 kW
Variable speed smart control					
Automatic Voltage Regulation (AVR)					
HiLight P2+	4	9	7	15	18
HiLight V2+	1	1	1	1	1
HiLight V3+	1	1	1	1	1
HiLight E3+	2	4	3	7	9



- Perfect fit
- Good choice

Choose the one that best fits your needs

	Segments	Energy Efficiency	Running hours	Area coverage	Easy movement	Lamps durability	Service interval	Transport efficiency
HiLight S2+	CONSTRUCTION QUARRY EVENTS	●	●	○	●	●	●	○
HiLight H6+	CONSTRUCTION QUARRY EVENTS	●	●	●	●	●	●	●
HiLight B6+	ROAD WORKS EVENTS	●	●	●	○	●	●	●
HiLight V4+	CONSTRUCTION QUARRY	●	●	●	●	●	●	○
HiLight V5+	CONSTRUCTION QUARRY	●	○	●	●	●	●	○
HiLight V4	CONSTRUCTION QUARRY	○	○	●	●	○	●	○
HiLight E3+	EVENTS ROAD WORKS	●	○	○	●	●	●	●
HiLight P2+	EVENTS	●	○	○	●	●	●	●
HiLight V2+/V3+	CONSTRUCTION ROAD WORKS	●	○	○	●	●	●	●
HiLight V4W	CONSTRUCTION QUARRY	●	●	●	●	○	●	○

● Best choice ○ Suitable

What's unique about our LED technology?

FUEL EFFICIENCY

LIFE SPAN
50.000 Hrs

LIGHT COVERAGE
UP TO 6.000 m²

COLOR RENDERING INDEX
≥ 85 OUT OF 100

INCREDIBLE LIGHT DISTRIBUTION

HEAVY DUTY PROTECTION

- LED HiLight tower lamps have an aluminum casting which provides heavy duty protection, even during transportation.
- The LED lamps have a high CRI (Color Rendering Index) score (> 85 out of 100).
- The specially designed directional optics of the LED HiLight range offer incredible light distribution.
- Our LED HiLight towers achieve up to 6.000 square-metres of light coverage with an average level of 20 luxes.
- LED lamps have a life expectancy of more than 50.000 hours.
- Our LED technology enables us to set the industry benchmark when it comes to fuel efficiency.

HiLight LED savings per year (per unit, compared to a metal halide light tower)

1.500 Liters -60%

4.800 Kilos -60%

23 Trees -60%

3 Bulbs -100%

(*) Savings will vary depending on comparison models.



		DIESEL						ELECTRIC					
Light coverage m2		2000 (average 10 luxes)	6000 (average 20 luxes)	5000 (average 20 luxes)	4000 (average 20 luxes)	5000 (average 20 luxes)	4000 (average 20 luxes)	4000 (average 20 luxes)	3000 (average 12 luxes)	2000 (average 10 luxes)	2000 (average 10 luxes)	2500 (average 10 luxes)	
Lamps		LED	LED	LED	LED	LED	Metal halide	Metal halide	LED	LED	LED	LED	
Mast		Vertical manual	Vertical hydraulic	Vertical hydraulic	Vertical manual	Vertical manual	Vertical manual	Vertical manual	Vertical manual	Vertical manual	Vertical manual	Vertical manual	
Extra features		Solar Noise and CO2 free	HardHat® body	Compact box	HardHat® canopy	HardHat® canopy	HardHat® canopy	HardHat® canopy	Electric	Electric	Electric	Electric	
Performance data													
Rated frequency	Hz	50 60	50	50 60	50 60	50 60	50 60	50 60	50 60	50	50	50	
Rated voltage	VAC	230 240	230	230 120	230 120	230 120	230 120	230 120	230 120	230	230	230	
Rated power (PRP)	kW	-	2,7	2,5 2,8	2,3 2,4	2,3 2,4	5,5 6	6 8	-	-	-	-	
Operating temperature (min/max)	°C	-5/50	-20 / 40	-20 / 40	-25 / 50	-25 / 50	-25 / 49	-25 / 50	-	-	-	-	
Sound power level (LwA)	dB(A)	-	82	82	88	86	92 94	87 89	-	-	-	-	
Sound pressure level (LpA) at 7m	dB(A)	-	55	55	65	63	71 73	63 64	-	-	-	-	
Energy Source													
Type		Solar	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Electric	Electric	Electric	Electric	
Model		-	Kubota Z482	Kubota Z482	Kubota Z482	Kubota Z482	Kubota Z482	Kubota Z482	-	-	-	-	
Speed	rpm	-	1500	1500 1800	1500 1800	1500 1800	3000 3600	1500 1800	-	-	-	-	
Rated net output (PRP)	kW	-	2,7	2,7 3	2,7 3	2,7 3	6,9 8,1	8 9,5	-	-	-	-	
Coolant		-	Water	Water	Water	Water	Water	Water	-	-	-	-	
Number of cylinders		-	2	2	2	2	2	3	-	-	-	-	
Alternator													
Model		-	Meccalte LT3/75	Meccalte LT3/75	Atlas Copco ACA132B*	Meccalte LT3/75	Sincro EK 2 MCT	Atlas Copco DP06/AG164	-	-	-	-	
Rated output	kVA	-	3,5 4,5	3,5 4,5	3 4	3,5 4,5	6 7,5	6 8	-	-	-	-	
Insulation / Enclosure protection	class/IP	-	H / 21	H / 21	H / 23	H / 21	H / 23	H / 23	-	-	-	-	
Energy Consumption													
Fuel tank capacity	l	11 22	125	125	110	110	110	160	-	-	-	-	
Autonomy	h	-	185	185	245	150	57 50	90	-	-	-	-	
Power output													
Auxiliary power	kW	-	1,2	1,2	1	1	1,4 2	2	-	-	-	-	
Lights													
Floodlights		LED	LED	LED	LED	LED	Metal halide	Metal halide	LED	LED	LED	LED	
Wattage	W	4 x 90	4 x 350	4 x 350	4 x 250	4 x 350	4 x 1000	4 x 1000	4 x 160 1x500	320	320	4 x 120	
Mast													
Type		Manual	Hydraulic	Hydraulic	Manual vertical, 5 section	Manual vertical, 5 section	Manual vertical, 5 section	Manual vertical, 5 section	Manual	Manual	Manual	Manual	
Rotation	degrees	340	340	340	360	360	360	360	0	0	0	0	
Maximum height	m	7	8	8	7,5	7,5	7,5	7,5	7	3,5	5	5	
Maximum speed wind	km/h	80	80	80	80	80	80	80	80	50	80	80	
Enclosure and trailer													
Type		-	Trailer with 4 point leveling system	EU Road homologated fix or adjustable towbar, or site trailer	-	DOT US Compliant Unibody trailer with 4 point leveling system. For EU homologated check availability			-	-	Heavy Duty Trailer with bumpers in PE	Heavy Duty Trailer with bumpers in PE	
Base frame		Spillage free frame				Open Frame / Spillage Free Frame Option	Spillage free frame			Galvanized	-	-	-
Enclosure		Galvanized steel canopy and powder coating paint	Galvanized steel canopy and powder coating paint	HardHat® doors	Galvanized steel canopy and powder coating paint	Gull-wing HardHat® doors			HardHat® canopy				
Dimensions and weight													
Dimensions in transport Fix Towbar(L x W x H)	m	3,55 x 1,7 x 2,3	2,09 x 1,29 x 2,5	1,16 x 1,16 x 2,5	1,67 x 1,10 x 2,50	1,67 x 1,10 x 2,50	1,67 x 1,10 x 2,50	1,8 x 1,35 x 2,97	1,13 x 0,76 x 2,2	0,5 x 0,5 x 2,2	1,1 x 0,85 x 2	1,1 x 0,85 x 2	
Weight	kg	1204	995	980	702	702	694	826	276	45	110	110	

(*) CE models, please consult

Product portfolio

GENERATORS

PORTABLE
1,6–12 kVA



SPECIALIZED
9–660* kVA



VERSATILE
9–1250* kVA



LARGE POWER
800–1450 kVA



*Multiple configurations available to produce power for any size application

DEWATERING PUMPS

ELECTRIC SUBMERSIBLE
250–16.200 l/min



SURFACE PUMPS
833–23.300 l/min



ZENERGIZE
45–500* kVA



Diesel and electric options available


ENERGY STORAGE SYSTEMS

LIGHT TOWERS

DIESEL



BATTERY



ELECTRIC



ONLINE SOLUTIONS

SHOP ONLINE PARTS ONLINE

Spare parts for power equipment. We handle your orders 24 hours a day.



POWER CONNECT

Scan the QR code on your machine, and go to the QR Connect Portal to find all the information about your machine.



LIGHT THE POWER: YOUR SIZING TOOL

A useful calculator to help you choose the best solution for your power and light needs.



FLEETLINK

Intelligent telematics is a system that helps optimize fleet usage and reduce maintenance, ultimately saving time and cutting operating costs.



PUMP SIZING CALCULATOR

With a few inputs, this pump sizing calculator will help you to compare dewatering submersible models and find the right one for you.



VISIT THE POWER ISLAND

Live a 360° experience to discover a selection of products and solutions that we offer, in an almost real environment.

