Every MUGEN

54102-XLT -K2S0 CARBON SHIFT KNOB / 6MT

		* The genuine lock nut in the f
In	stallation • Handling manual	
Thank you for purchasing the MUG	EN product.	
Please be sure to understand the fo	ollowing precautions before installing.	
Please be sure to give this manual to the cust	omer after installation.	
please note		- 1
1. Immediately after unpacking, check that the content	s of the package (see the component list) are not missing or damaged.	
2 Before mounting, check the screw diameter of		
[Applicable model)	ACCORD Euro R (CL7)	
ę , , , 	CIVIC TYPE R (FD2)	
	CIVIC TYPER EURO CFN2)	
	CR-Z ct • Bl ack / Master I abe I 6MT car, ct 6MT car (ZF1,2)	
	INTEGRA TYPE R (DC5)	
	S2000 (AP1 • 2)	
	S660 (DBA-JW5-100) ct 6 MT car	
	CIVIC TYPE R CFK2)	
Please note that we do not bear any responsibility. T 351-8586 2-15-11 Hiza M-TEC Co., 00 (excludin TEL. O 45 To customers	sembly, defects and accidents due to misuse, we will we Responsibility oricho, Asaka City, Saitama Prefecture Ltd. Product Division Sales Section 1 [Business Hours 10: 00 ~ 17: y Saturdays, Sundays, and holidays)] 0-46 2-3131 FAX. O 48- 46 2-31 21 rking in the hot summer sun. Be careful of burns when using	Pure mo M10 x Specifie * CR-Z
Please give me. 2. Periodically check the shift knob for loosen	and aback the mounting condition	
2. Penducally check the shift knob for loosen		
[Kiso Naribe Akira] No. PARTS NAME. ① Shift knob	ату. 1 0 Сара на 1 	
[Necessary tools]		
CR-Z	Other applicable models	
· 1 7mm spanner	· 14mm spanner	
Torque wrench (17mm spanner type)	 Torque wrench (14mm spanner type) 	③ Check if the installation is completed.

[Ear size] t left]

Remove the genuine shift knob

* Sa - See the screw manual.

(2) Using a genuine lock nut, adjust the position of the shift knob with a spanner and tighten it to the specified torque.

* The genuine lock nut in the figure is for CR-Z, but other applicable models should be installed in the same procedure.



