

DRENEC SMOCK NYLPECHE

CE

Technical data

PROTECTION FRAMEWORK / EN 343: 2003 + A1: 2007

This garment is designed to protect from bad weather, precipitations in the form of rain or snow, fog, spray and moisture on the ground.

Self-grip adjustment tab ~

<u>For professional use</u>: **Fishing - agriculture - industry - cleaning** or other activities requiring this kind of protection.

THIS ARTICLE IS A

CATEGORY 1 PPE

And complies with EU regulation 2016/425

PPE = Personal Protective Equipment

PERFORMANCE



The assembled parts are High Frequency welded, guaranteeing a waterproof garment.

- Water penetration resistance ≥ 13,000 Pa = Class 3
- Evaporative resistance = n/a
 Ret > 40 m².Pa/W = Class 1

RESTRICTIONS ON USE

(specified in the EN 343: 2007 standard)

"A maximum continuous wear time is recommended for 1 full suit (jacket + trousers) without a thermal lining"

Ambient work	Time
temperature in °C	in minutes
25	60
20	75
15	100
10	240
5	Unlimited

ILLUSTRATION AND INSTRUCTIONS

Surrounding hood with integrated visor and drawstring

PRINCIPAL MATERIALS

Nylpêche fabric - 485 g/m² Composition: 69 % PVC – 31 % Polyester Double-sided coating

Features:

- WATERPROOF
- HEAVY DUTY

Chest pocket with double self-grip flap. Drawstring at bottom of smock

For maximum protection, the DRENEC NYLPECHE smock can be worn with PPE classed trousers or bib & braces.

INSTRUCTIONS

CARE



- STORAGE
- Do not leave in package in damp surroundings.
- Store in dry surroundings at room temperature.
- Keep away from strong heat and flames.

SIZE TABLE

Guideline				
Size	Size of the	person's body (in cm)	measurements of clothing (in cm)	
	Stature	Chest size	Chest size	
XS	150-165	78-86	120	
S	165-170	86-94	134	
M	170-180	94-102	144	
L	175-185	102-110	160	
XL	180-190	110-124	168	
XXL	185+	124-134	182	



Colour: yellow, green

<u>Sizes</u>: XS – S – M – L –

XL - XXL

The lifespan of the garment is linked to conditions of use and the quality of its care.