

**SECTION 1: Identification of the substance/mixture and of the company/  
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Epoxy Filler 1500 Component B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.
- Application of the substance / the mixture  
See our technical datasheet for application details of this product.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31-(0)297-360366  
fax +31-(0)297-342078  
email: r&d@epifanes.nl
- Further information obtainable from: environment protection department
- 1.4 Emergency telephone number:  
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: r&d@epifanes.nl  
Phone the National Poisons Information: Tel. +31 30 2748888

**SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B            H314 Causes severe skin burns and eye damage.



GHS07

Acute Tox. 4            H302 Harmful if swallowed.

Skin Sens. 1            H317 May cause an allergic skin reaction.

Aquatic Chronic 3    H412 Harmful to aquatic life with long lasting effects.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



C; Corrosive

R34: Causes burns.



Xi; Sensitising

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- Classification system:  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 1)

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
 The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS05



GHS07

- Signal word Danger
- Hazard-determining components of labelling:  
 Benzyl alcohol  
 3-aminomethyl-3,5,5-trimethylcyclohexylamine  
 m-phenylenebis(methylamine)  
 3-aminopropyldiethylamine
- Hazard statements  
 H302 Harmful if swallowed.  
 H314 Causes severe skin burns and eye damage.  
 H317 May cause an allergic skin reaction.  
 H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements  
 P102 Keep out of reach of children.  
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**

- 3.2 Chemical characterization: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 7727-43-7	barium sulphate, natural	25-50%
EINECS: 231-784-4	substance with a Community workplace	
Reg.nr.: 01-2119491274-35	exposure limit	

(Contd. on page 3)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 30.07.2014

Version number 5

Revision: 30.07.2014

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 2)

CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38	Benzyl alcohol Xn R20/22 Xi R43 Acute Tox. 4, H302; Acute Tox. 4, H332	10-25%
CAS: 98-54-4 EINECS: 202-679-0 Reg.nr.: 01-2119489419-21	4-tert-butylphenol Xi R36/37/38 N R51/53 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine C R34 Xn R21/22 Xi R43 R52/53 Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 Aquatic Chronic 3, H412	2.5-10%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) C R34 Xn R22 Skin Corr. 1B, H314 Acute Tox. 4, H302	2.5-10%
CAS: 104-78-9 EINECS: 203-236-4 Index number: 612-062-00-1 Reg.nr.: 01-2119965402-39	3-aminopropyldiethylamine C R34 Xn R21/22 Xi R43 R10 Flam. Liq. 3, H226 Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≤ 2.5%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Xn R22 Xi R36/38 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤ 2.5%
CAS: 121158-58-5 EINECS: 203-236-4 Index number: 612-062-00-1 Reg.nr.: 01-2119513207-49	dodecylphenol C R35 Xn R62 N R50/53 Repr. 2, H361 Skin Corr. 1A, H314 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≤ 2.5%

Additional information:

For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 4)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 3)

**SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:  
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:  
Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture  
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

**SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures  
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling  
No special precautions are necessary if used correctly.

(Contd. on page 5)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 4)

- Information about fire - and explosion protection:  
No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- Additional information about design of technical facilities:  
No further data; see item 7.

· 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

Inhalative	Tijd gewogen gemiddelde over 8 uur / Exposure time	4 mg/m <sup>3</sup> (general population)
------------	--	---

7727-43-7 barium sulphate, natural

WEL	Long-term value: 10* 4** mg/m <sup>3</sup> *inhalable dust **respirable dust
-----	---

· DNELs

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Inhalative	Acute - systemic effects, worker	20.1 mg/m <sup>3</sup> (Werker/Worker)
	Acute-local effects, worker	20.1 mg/m <sup>3</sup> (Werker/Worker)

· PNECs

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Aquatic compartment - freshwater	0.06 mg/L (Consument)
Aquatic compartment - marine water	0.006 mg/L (4)
Aquatic compartment - sediment in freshwater	5.784 mg/kg sed dw (3)
Aquatic compartment - sediment in marine water	0.578 mg/kg sed dw (5)
Aquatic compartment - water, intermittent releases	0.23 mg/L (intermittent release water)
Sewage treatment plant	3.18 mg/L (7)
Terrestrial compartment - soil	1.121 mg/kg dw (8)

1477-55-0 m-phenylenebis(methylamine)

Aquatic compartment - freshwater	0.094 mg/L (Consument)
Aquatic compartment - marine water	0.0094 mg/L (4)
Aquatic compartment - sediment in freshwater	0.43 mg/kg sed dw (3)
Aquatic compartment - sediment in marine water	0.043 mg/kg sed dw (5)
Aquatic compartment - water, intermittent releases	0.152 mg/L (intermittent release water)
Sewage treatment plant	10 mg/L (7)
Terrestrial compartment - soil	0.045 mg/kg dw (8)

- Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 5)

- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
  - As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
  - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:
 

Form:	Solid
Colour:	According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Not determined.
- Change in condition
 

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	205 °C
- Flash point: 101 °C
- Flammability (solid, gaseous): Not applicable.
- Ignition temperature: 435 °C

(Contd. on page 7)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 6)

· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20 °C:	0.1 hPa
· Density at 20 °C:	1.413 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	22.2 %
VOC content:	22.2 %
	VOC content: 314.0 g/l / 2.62 lb/gl
Solids content:	67.8 %
· 9.2 Other information	No further relevant information available.

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:  
No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevant for classification:

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg bw (rat)
Dermal	LD50	2000 mg/kg bw (rabbit)

(Contd. on page 8)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 7)

98-54-4 4-tert-butylphenol		
Oral	LD50	2951 mg/kg bw (rat)
Dermal	LD50	2288 mg/kg bw (rabbit)
1477-55-0 m-phenylenebis(methylamine)		
Oral	LD50	1040 mg/kg bw (rat)
104-78-9 3-aminopropyldiethylamine		
Oral	LD50	1410 mg/kg bw (rat)
Dermal	LD50	750 mg/kg bw (rabbit)

- Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

**SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity:
 

1477-55-0 m-phenylenebis(methylamine)		
Inhalative	LC50/4 h	2.4 mg/l (rat)
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes:  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralized.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

**SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 8)

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- 14.1 UN-Number
- ADR, IMDG, IATA

UN2735

- 14.2 UN proper shipping name
- ADR

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
(dodecylphenol, m-phenylenebis(methylamine))  
POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
(dodecylphenol, m-phenylenebis(methylamine))

- 14.3 Transport hazard class(es)
- ADR



- Class
- Label

8 (C9) Corrosive substances.  
8

- IMDG, IATA



- Class
- Label

8 Corrosive substances.  
8

- 14.4 Packing group
- ADR, IMDG, IATA

III

- 14.5 Environmental hazards:
- Marine pollutant:

No

- 14.6 Special precautions for user
- Danger code (Kemler):
- EMS Number:
- Segregation groups

Warning: Corrosive substances.  
80  
F-A, S-B  
Alkalis

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 10)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 9)

· Transport/Additional information:

· ADR

- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code E

· IMDG

- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation": UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S. (dodecylphenol, m-phenylenebis(methylamine)), 8, III

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Technical instructions (air):
 

Class	Share in %
NK	10-25
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.

(Contd. on page 11)

Trade name: Epifanes Epoxy Filler 1500 Component B

(Contd. of page 10)

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
R10	Flammable.
R20/22	Harmful by inhalation and if swallowed.
R21/22	Harmful in contact with skin and if swallowed.
R22	Harmful if swallowed.
R34	Causes burns.
R35	Causes severe burns.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

\* Data compared to the previous version altered.