

## Specification guide - Creig XS/S/M

Model	Creig XS	Creig S	Creig M
<b>Size</b>	27.5" wheels, 14" frame	29" wheels, 15" frame	29" wheels, 16.5" frame
<b>Colour</b>	Gloss Blue	Gloss Blue	Gloss Blue
<b>Age</b>	Adult	Adult	Adult
<b>Approx Weight</b>	11.5kg	11.8kg	11.9kg
<b>Frame</b>	6061 aluminium	6061 aluminium	6061 aluminium
<b>Fork</b>	RockShox Judy Gold RL Solo Air, 100mm travel, lockout and rebound adjustment	RockShox Judy Gold RL Solo Air, 100mm travel, lockout and rebound adjustment	RockShox Judy Gold RL Solo Air, 100mm travel, lockout and rebound adjustment
<b>Headset</b>	1-1/8" Integrated	1-1/8" Integrated	1-1/8" Integrated
<b>Handlebar</b>	Islabikes aluminium flat bar, 31.8mm, 680mm	Islabikes aluminium flat bar, 31.8mm, 720mm	Islabikes aluminium flat bar, 31.8mm, 740mm
<b>Stem</b>	Islabikes aluminium, 40mm, stainless steel bolts	Islabikes aluminium, 40mm, stainless steel bolts	Islabikes aluminium, 40mm, stainless steel bolts
<b>Grip</b>	Islabikes ergonomic lock-on grips	Islabikes ergonomic lock-on grips	Islabikes ergonomic lock-on grips
<b>Seatpost</b>	Aluminium inline, 27.2" x 350mm	Aluminium inline, 27.2" x 350mm	Aluminium inline, 27.2" x 400mm
<b>Saddle</b>	Islabikes ergonomic adults saddle	Islabikes ergonomic adults saddle	Islabikes ergonomic adults saddle
<b>Brakes</b>	Tektro hydraulic with 140mm rear and 160mm front disc	Tektro hydraulic with 140mm rear and 160mm front disc	Tektro hydraulic with 140mm rear and 160mm front disc
<b>Brake Lever</b>	Tektro hydraulic	Tektro hydraulic	Tektro hydraulic
<b>Rims</b>	Stan's Crest S2, 28 hole, tubeless compatible	Stan's Crest S2, 28 hole, tubeless compatible	Stan's Crest S2, 28 hole, tubeless compatible
<b>Tyres</b>	Veel Rail Roco 27.5" (57-584), 120TPI, Folding bead	Veel Rail Roco 29" (57-622), 120TPI, Folding bead	Veel Rail Roco 29" (57-622), 120TPI, Folding bead
<b>Spokes</b>	Stainless steel	Stainless steel	Stainless steel
<b>Hubs</b>	Aluminium disc, QR	Aluminium disc, QR	Aluminium disc, QR
<b>Cranks</b>	Islabikes aluminium, SRAM fit direct mount, 155mm, 30mm aluminum axle	Islabikes aluminium, SRAM fit direct mount, 160mm, 30mm aluminum axle	Islabikes aluminium, SRAM fit direct mount, 165mm, 30mm aluminum axle
<b>Chainring</b>	Direct mount, narrow/wide 30t	Direct mount, narrow/wide 30t	Direct mount, narrow/wide 30t
<b>Bottom Bracket</b>	30mm external, sealed bearings	30mm external, sealed bearings	30mm external, sealed bearings
<b>Rear Derailleur</b>	Microshift, Advent X, 10sp, RD+	Microshift, Advent X, 10sp, RD+	Microshift, Advent X, 10sp, RD+
<b>Shifter</b>	Microshift, Advent X, 10sp	Microshift, Advent X, 10sp	Microshift, Advent X, 10sp
<b>Chain</b>	KMC, 10sp	KMC, 10sp	KMC, 10sp
<b>Cassette</b>	Microshift, Advent X, 10sp, 11-48t	Microshift, Advent X, 10sp, 11-48t	Microshift, Advent X, 10sp, 11-48t
<b>Pedals</b>	Islabikes proportional resin flats with ball bearings	Islabikes proportional resin flats with ball bearings	Islabikes proportional resin flats with ball bearings

\* Specifications are subject to change without notice