

# Specification guide Beinn 29

<b>Model</b>	<b>Beinn 29</b>
<b>Colour</b>	Silver
<b>Wheel size</b>	700c wheels
<b>Frame</b>	7005 T6 heat treated aluminium
<b>Forks</b>	Lightweight cro-moly blades and steerer with mudguard eyes
<b>Headset</b>	1 1/8" ahead
<b>Stem</b>	Islabikes aluminium ahead flip flop 70mm
<b>Grips</b>	File pattern grips
<b>Seatpost</b>	Aluminium micro adjust
<b>Saddle</b>	Islabikes proportional saddle
<b>Brakes</b>	Sram BB5
<b>Brake levers</b>	Aluminium levers
<b>Rims</b>	Islabikes aluminium double wall, 32 hole
<b>Spokes</b>	Stainless steel, black
<b>Hubs</b>	Aluminium quick release with seals
<b>Tyres</b>	Vee Rubber, East Street 28 x 1.55 (38-700), 72TPI with wire bead
<b>Chainring</b>	Aluminium 32t
<b>Chainguard</b>	Aluminium single guard
<b>Bottom bracket</b>	Cartridge with sealed bearings
<b>Pedals</b>	Aluminium with ball bearings

<b>Rear mech</b>	Sram X5 medium arm
<b>Front mech</b>	None
<b>Shifter</b>	Sram X5 trigger 10sp
<b>Freewheel / Cassette</b>	Sram 10sp 11 – 40t cassette
<b>Max Weight</b> (rider and luggage)	125kg

This bike has been designed to be ridden on smooth paved, unpaved, gravel roads and off-road trails with moderate gradients. Contact with irregular terrain and loss of tyre contact with the ground may occur. Drops are intended to be limited to less than 15cm.

## Compare the Beinn 29 Small, Medium and Large

Model	Beinn 29 Small	Beinn 29 Medium	Beinn 29 Large
<b>Frame Size</b>	16"	18"	20"
<b>Approx weight</b> (including pedals)	11.8kg (26lbs)	12kg (26lbs 7oz)	12.14kg (26lbs 12oz)
<b>Handlebar</b>	Aluminium riser bar, 620mm	Aluminium riser bar, 650mm	Aluminium riser bar, 660mm
<b>Cranks</b>	Prowheel, 165mm	Prowheel, 170mm	Prowheel, 175mm

\*All specifications subject to change without notice