

## Specification guide - Jimi S/M/L

Model	Jimi S	Jimi M	Jimi L
<b>Size</b>	27.5" wheels, 15" frame	29" wheels, 16.5" frame	29" wheels, 18.5" frame
<b>Colour</b>	Gloss ash grey	Gloss ash grey	Gloss ash grey
<b>Age</b>	Adult	Adult	Adult
<b>Approx weight</b>	9.9kg	9.9kg	9.9kg
<b>Frame</b>	6061 aluminium	6061 aluminium	6061 aluminium
<b>Forks</b>	Islabikes carbon fork tapered steerer, 12mm straight thru axle and clearance for Mudhugger guard	Islabikes carbon fork tapered steerer, 12mm straight thru axle and clearance for Mudhugger guard	Islabikes carbon fork tapered steerer, 12mm straight thru axle and clearance for Mudhugger guard
<b>Headset</b>	Integrated sealed bearings	Integrated sealed bearings	Integrated sealed bearings
<b>Handlebar</b>	Aluminium double butted riser 680mm	Aluminium double butted riser 700mm	Aluminium double butted riser 720mm
<b>Stem</b>	Aluminium 60mm, 17-deg reversible for height adjustment	Aluminium 60mm, 17-deg reversible for height adjustment	Aluminium 60mm, 17-deg reversible for height adjustment
<b>Grips</b>	Lock on	Lock on	Lock on
<b>Seatpost</b>	Aluminium 27.2mm, 400mm	Aluminium 27.2mm, 400mm	Aluminium 27.2mm, 400mm
<b>Saddle</b>	Islabikes saddle	Islabikes saddle	Islabikes saddle
<b>Brakes</b>	Tektro hydraulic with 140mm rear and 160mm front disc	Tektro hydraulic with 140mm rear and 160mm front disc	Tektro hydraulic with 140mm rear and 160mm front disc
<b>Brake levers</b>	Tektro hydraulic	Tektro hydraulic	Tektro hydraulic
<b>Rims</b>	Islabikes "Easy-Tyre-Change", disc, 28-hole	Islabikes "Easy-Tyre-Change", disc, 32-hole	Islabikes "Easy-Tyre-Change", disc, 32-hole
<b>Tyres</b>	Veel Rail Roco 27.5" (57-584), 120TPI, Folding bead	Veel Rail Roco 29" (57-622), 120TPI, Folding bead	Veel Rail Roco 29" (57-622), 120TPI, Folding bead
<b>Spokes</b>	Stainless steel	Stainless steel	Stainless steel
<b>Hubs</b>	Islabikes sealed bearing, disc, 12mm thru-axle	Islabikes sealed bearing, disc, 12mm thru-axle	Islabikes sealed bearing, disc, 12mm thru-axle
<b>Cranks</b>	Islabikes Sram fit direct mount, 30mm axle, low Q-factor, 160mm	Islabikes Sram fit direct mount, 30mm axle, low Q-factor, 165mm	Islabikes Sram fit direct mount, 30mm axle, low Q-factor, 170mm
<b>Chainring</b>	Direct mount, narrow/wide 26t	Direct mount, narrow/wide 26t	Direct mount, narrow/wide 26t
<b>Chainguard</b>	None	None	None
<b>Bottom bracket</b>	30mm external, sealed bearings	30mm external, sealed bearings	30mm external, sealed bearings
<b>Rear derailleur</b>	Sram X4, 8spd	Sram X4, 8spd	Sram X4, 8spd
<b>Shifter</b>	Sram X4, Gripshift, 8spd	Sram X4, Gripshift, 8spd	Sram X4, Gripshift, 8spd
<b>Chain</b>	KMC, 8spd	KMC, 8spd	KMC, 8spd
<b>Freewheel / Cassette</b>	Sunrace 8spd 11-40T	Sunrace 8spd 11-40T	Sunrace 8spd 11-40T
<b>Pedals</b>	Islabikes proportional resin flats with ball bearings	Islabikes proportional resin flats with ball bearings	Islabikes proportional resin flats with ball bearings

\* Specifications are subject to change without notice