MATERIAL SAFETY DATA SHEET

W-800 ACRYLIC LATEX (1 GAL)

6/13/2013

Page: 1

HMIS CODES: H F R P PRODUCT NAME: W-800 ACRYLIC LATEX (1 GAL)

PRODUCT CODE: WE0780010. 1 0 0 B

MANUFACTURER'S NAME: Weco

ADDRESS : Baldorioty #43

Cidra, P.R. 00739

EMERGENCY PHONE : 1-800-424-9300 DATE PRINTED : 6/13/2013

INFORMATION PHONE : 1-787-739-3751 NAME OF PREPARER: WECO LABORATORY

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

VAPOR PRESSURE

REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP

*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***

+ Indicates a product that is considered hazardous material under the OSHA Hazardous Comunication Standard (29 CFR 1910.1200).

* Indicates Toxic Chemical(s) subject to reporting requirements of section 313 of Title III of CFR 372.

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ------

BOILING RANGE: n/a SPECIFIC GRAVITY (H2O=1): 1.02

VAPOR DENSITY: LIGHTER THAN AIR. EVAPORATION RATE: N/A

COATING V.O.C.: 0.11 lb/gl MATERIAL V.O.C.: 0.02 lb/gl

SOLUBILITY IN WATER: SOLUBLE

APPEARANCE AND ODOR: LIQUID - LOW ODOR

METHOD USED: N/A FLASH POINT: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a

EXTINGUISHING MEDIA: N/A

SPECIAL FIREFIGHTING PROCEDURES

CUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTION EQUIPMENT HEAT INCLUDING SELFCONTIANED BREATHING APPARATUS. WATER SPRAY MAY BEIN EFFECTIVE. IF WATER IS USED, FOGNOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD-UP CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE DURING EMERGENCY CONDITIONS, OVEREXPESURE TO DECOMPOSITION PRODUCT MAY CAUSE A HEALTH HAZARD. OBTAIN ATTENTION.

STABILITY: STABLE CONDITIONS TO AVOID

NONE

INCOMPATIBILITY (MATERIALS TO AVOID)

MATERIAL SAFETY DATA SHEET

W-800 ACRYLIC LATEX (1 GAL)

Page: 2 6/13/2013

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE, CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IRRITATION OF THE RESPIRATIORY TRACT, HEADACHE, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

IN CASE OF EYE OR SKIN CONTACT; SEVERE IRRITATION, TEARING AND REDNESS.

FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

REMOVE WITH SOAP AND WATER. REMOVED SOILED CLOTHING.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA AND DIARRHEA. DRINK 1 OR 2 GLASSES OF WATER. CONSULT PHYSICIAN OF POISON CONTROL CENTER IMMEDIATELY. TREAT SYMTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OR SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED:

NO

NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE WHEN USED IN ACCORDANCE WITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: REMOVE TO FRESH AIR. IF IN EYES: IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF OF SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTED. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING UNLESS THE PHYSICIANS INSTRUCTIONS.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER, BEFORE ATTEMPTING CLEAN UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA FORM. CONTAIN SPILLED AND REMOVE WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD

DIPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

MATERIAL SAFETY DATA SHEET

W-800 ACRYLIC LATEX (1 GAL)

Page: 3 6/13/2013

STORE BELOW 100 F AND KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT USE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.



NONE

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS, SPRAY MIST OF SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION, AND DURING SANDING OR GRINDING OPERATION, USE NOISH/NSHA APROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARS IN THE MIXING.

PROTECTIVE GLOVES

CHEMICALLY RESISTANT GLOVES SHOULD BE WORN WHENEVER THIS MATERIAL IS HANDLING.

EYE PROTECTION

SAFETY EYEWEAR WITH SPLASHGUARDS ARE RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED. USE CHEMICALLY RESISTAN APRON OR OTHER IMPERVIOUS CLOTHING TO AVOID SKIN CONTACT.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, OR USING THE BATHROOM.

UN NUMBER

N/A

PROPER SHIPPING NAME

Non Hazardous, Non Flammable

HAZARD CLASS

N/A

PACKING GROUP

n/a

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY THIS COMPANY TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABLILITY FOR ITS ACCURANCY. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED THE ONLY ONES WHICH EXIST. THE MANNER OF THAT USE AND WHEATHER THERE IS ANY INFRIGEMENT OF PATENTS IS THE RESPONSABILITY OF THE USER.