



Model: Mammoth X 500 **SO**

VM MB MMX 500-0-500 200

SPECIFICATIONS: CLASS 2 EBIKE

Motor(s)

Front Motor Brushless BAFANG™ 52V 500W gear hub motor UPGRADED Rear Motor Brushless BAFANG™ 52V 500W gear hub motor UPGRADED

Torque 80 Nm x 2 Max torque

Battery

Battery 52V 20Ah Samsung™ lithium-ion battery UPGRADED

> Optional secondary 52V 15AH battery UPGRADE OPTION 1040 Wh Hr MONSTER! With secondary - 1820 Wh Hr! Approx. 52 miles or 84 kilometres; 150 kms with secondary!

4-6 hrs.

Wiring High quality, weather-resistent connectors and wiring harness.

Display

Kingmeter™ K5266 color display with logo, Bluetooth UPGRADED Display

Braking System

USB plugin

Brake pad

Battery Watt Hours

Distance per charge Battery charge time

Front and rear Tektro™ hydraulic HD-E350 disk brakes UPGRADED Brake components Light Wave Type (TR160-7) - High Heat Dispersion & Heat Tolerance Brake Roter

Metal Ceramic Compound

Frame

6061 "aircraft" aluminum alloy frame Frame

Front fork BOXER hydraulic aluminum alloy suspension with lock-out

Wheels

Rims Double Alloy Aluminum with 12 gauge spokes both front and rear

Front Tire MAXXIS™ mountain 26" x 4.8" UPGRADED Rear Tire MAXXIS™ mountain 26" x 4.8" UPGRADED

26" x 4.8" Max Tire Size

Drivetrain

SHIMANO™ Acera 7 speed Shifters SHIMANO™ Acera 7 speed Rear Derailleur

Crank 48T aluminum alloy SHIMANO™ 7 speed Cassette/Freewheel

Chainring Prowheel™ aluminum alloy 38T 170 mm

KMC™ anti-rust chain Chain

GYBEARING™ aluminum alloy **Pedals**

Other Equipment

Velo™ comfort UPGRADED Saddle

Handle bar Aluminum alloy

Adjustable aluminum alloy stem Stem Seat post PROMAX suspension seat post **UPGRADE**

Front and rear lights Wired LED with brake (rear) UPGRADE

Standard Charger 52V 4Amp ST quick charger. Voltage input 110V~230V UPGRADED

Dimensions

Weight

5'4" - 6'2" Suitable rider height Length: 76" Dimensions

Handlebar height: 43.3"

Seat tube: 19" Wheelbase: 47.6" 80 lbs. with battery

Max. load 330 lbs.

Winter Ready!

• Headset travel stop - standard!

The ULTIMATE AWD electric bicycle, the

providing exceptional power and torque for

Vamoose Mammoth comes with dual 52V 500W motors (front and rear)

mud-slinging or crushing fresh powder!


The Vamoose AWD Mammoth was developed with a love of Canadian outdoors. Ready for any weather, the AWD Mammoth is as comfortable in heavy snow, as pulling through mud, or on a ravine trail. Built with outdoor enthusiasts in mind, the Mammoth has been outfitted for all Canadian seasons.



UPGRADED - KINGMETER COLOUR DISPLAY

The Vamoose Super Mammoth comes standard with the KINGMETER™ K5266 colour LCD that displays speed, battery life, error codes, as well as provides an USB connection.





• Headset travel stop - standard!

Winter Ready!

The Vamoose AWD Mammoth was developed with a love of Canadian outdoors. Ready for any weather, the AWD Mammoth is as comfortable in heavy snow, as pulling through mud, or on a ravine trail. Built with outdoor enthusiasts in mind, the Mammoth has been outfitted for all Canadian seasons.



Model: Mammoth X 500 ST

VM MB MMX 500-0-500 200

SPECIFICATIONS: CLASS 2 EBIKE

Motor(s)

Brushless BAFANG™ 52V 500W gear hub motor UPGRADED Front Motor Rear Motor Brushless BAFANG™ 52V 500W gear hub motor UPGRADED

Torque 80 Nm x 2 Max torque

Battery

52V 20Ah Samsung™ lithium-ion battery UPGRADED Battery

> Optional secondary 52V 15AH battery UPGRADE OPTION 1040 Wh Hr MONSTER! With secondary - 1820 Wh Hr! Approx. 52 miles or 84 kilometres; 150 kms with secondary!

Distance per charge Battery charge time 4-6 hrs.

High quality, weather-resistent connectors and wiring harness.

Wiring Display

Kingmeter™ K5266 color display with logo, Bluetooth UPGRADED Display

USB plugin Yes UPGRADED

Braking System

Battery Watt Hours

Front and rear Tektro™ hydraulic HD-E350 disk brakes UPGRADED Brake components Brake Roter Light Wave Type (TR160-7) - High Heat Dispersion & Heat Tolerance

Brake pad Metal Ceramic Compound

Frame

6061 "aircraft" aluminum alloy frame Frame

Front fork BOXER hydraulic aluminum alloy suspension with lock-out

Wheels

Rims Double Alloy Aluminum with 12 gauge spokes both front and rear

MAXXIS™ mountain 26" x 4.8" UPGRADED Front Tire MAXXIS™ mountain 26" x 4.8" UPGRADED Rear Tire

26" x 4.8" Max Tire Size

Drivetrain

SHIMANO™ Acera 7 speed Shifters SHIMANO™ Acera 7 speed Rear Derailleur Crank 48T aluminum alloy

Cassette/Freewheel SHIMANO™ 7 speed

Prowheel™ aluminum alloy 38T 170 mm Chainring

KMC™ anti-rust chain Chain

GYBEARING™ aluminum alloy **Pedals**

Other Equipment

Velo™ comfort UPGRADED Saddle

Handle bar Aluminum alloy

Adjustable aluminum alloy stem Stem

PROMAX suspension seat post **UPGRADE** Seat post Front and rear lights Wired LED with brake (rear) UPGRADE

52V 4Amp ST quick charger. Voltage input 110V~230V UPGRADED Standard Charger

Dimensions

Weight

5'4" - 6'2" Suitable rider height **Dimensions** Length: 76"

Handlebar height: 43.3"

Seat tube: 19" Wheelbase: 47.6" 80 lbs. with battery

Max. load 330 lbs.



UPGRADED - KINGMETER COLOUR DISPLAY

The Vamoose Super Mammoth comes standard with the KINGMETER™ K5266 colour LCD that displays speed, battery life, error codes, as well as provides an USB connection.