

A full suspension, 48V 500W mountain crusher, the Vamoose ODIN Mountain Bike brings enjoyment to trails full of bumps and chatter. With its impact reducing front and rear shocks that bear the brunt of trail impacts, the ODIN has been designed to dramatically reduce the impact on the rider while increasing traction and creating a very forgiving and enjoyable ride.

The Vamoose ODIN is a purpose-built Mountain Crusher. 500W motor provides the Maximum Power afforded under Canadian Law.

Model: ODIN 4.2 MTB

VM-OD 42 48-500-160

SPECIFICATIONS: CLASS 2 EBIKE

| SPECIFICATIONS: CLASS 2 EBIKE | |
|-------------------------------|--|
| Motor(s) | |
| Front Motor | N/A |
| Rear Motor Controller | Brushless BAFANG™ 48V 500W gear hub motor UPGRADE 48V 18A intelligent brushless |
| Torque | 80 Nm Max torque with CADENCE sensor |
| | |
| Battery | 401/4 CAL Concern TH lithium inclusion between UDODAD5 |
| Battery Battery Watt Hours | 48V 16Ah Samsung™ lithium-ion battery UPGRADE 768 Wh - a MONSTER! |
| Distance per charge | Approx. 38 miles or 61 kilometres |
| Battery charge time | 4-6 hrs. |
| Wiring | High quality, weather-resistent connectors and wiring harness. |
| Display | |
| Display | CDC6 display UPGRADE |
| USB plugin | Yes |
| Braking System | |
| Braking Components | Front and rear Tektro™ HD-E350 Hydraulic Brake UPGRADE |
| Brake Roter | Front and rear Tektro™ 180mm |
| Brake pad | Metallic |
| Frameset | |
| Frame | 6061 "aircraft" aluminum alloy frame |
| Front fork | BOXER™ Suspension Front Fork, with lockout |
| Rear Shock | EXA FORM™ A5 |
| Wheels | |
| Rims | Custom build double-layer drilled aluminum alloy |
| Front tire | 26" x 4.0" KENDA™ Krusade anti-puncture |
| Rear tire Max tire size | 26" x 4.0" KENDA™ Krusade anti-puncture 26" x 4.0" |
| | 20 / 1.0 |
| Drivetrain Shifters | CHIMANOM Altur 7 Speed |
| Snifters Rear Derailleur | SHIMANO™ Altus 7-Speed SHIMANO™ Altus 7-Speed |
| Crank | Aluminum alloy 48T |
| Cassette/Freewheel | SHIMANO [™] 7 Speed anti-rust |
| Chainring | PROMAX™ 48T |
| Chain | Anti-rust |
| Pedals | Aluminum Alloy Black |
| Other Equipment | |
| Saddle | Velo™ Plush silicon gel |
| Handle Bar Stem | Alloy straight |
| Stem Seat post | Alloy adjustable PROMAX ™ 300mm aluminum alloy, Tube diameter: 30.4mm |
| Kickstand | Custom built side kick |
| Headlight | Spannis™ LED <mark>UPGRADE</mark> |
| Tail light | Spannis [™] LED with brake UPGRADE |
| Charger | 48V 2Amp Smart Quick Charger. Voltage input: 110V~230V |
| Dimensions | |
| Suitable rider height | 5'4" - 6'4" |
| Dimensions | Length: 71" |
| | Handlebar height: 41.5" |
| | Max seat height: 41" Min. seat height: 33" |
| | With Seat Height. 55 |

Fenders & Rear Rack Standard!

Max. load



Seat tube: 18.5"

Wheelbase: 45" Handlebar reach: 17"

300 lbs.

