

# **SUNFOUNT SF 10**

# Standard fountain solution for sheetfed printing

#### **KEY CHARACTERISTICS**

Suited for all water qualities

Dosage: 2 - 3 %IPA Dosage: 8 - 12 %

Suited for conventional ink

Recommended pH value: 4,8 - 5,2

Standard fountain solution

Density: 1,060 g/ml

#### **PACKAGING**

27 kg jerrycan 10 kg jerrycan

# **FEATURES AND BENEFITS**

#### Stable ink/water balance

- · Consistent print quality
- No over-emulsification
- Wide printing latitude

## Strong buffer

 Ensures a stable pH-value with varying water qualities and different types of paper

## Avoid calcium build up on roller and blankets

- Reduced standstills
- Increased production

#### **INSTRUCTIONS FOR USE**

Clean the dampening circuit before using the fountain solution.

Set the dosing equipment for correct dosage of the fountain solution.

After completion and circulation through the system check for pH and conductivity and compare with the target concentration values.

### TRANSPORT & STORAGE

Store at room temperature.

Protect from freezing, heat above 35 °C and direct s unlight. For details about health and safety, please consult the MSDS.

Version 1.0, state 2/12/2015 - Our Products are intended for sale to professional users. The information herein is general information designed to assist customers in determining the suitability of our products for their applications. All recommendations are made without guarantee, since the application and conditions of use are beyond our control. We recommend that customers satisfy themselves that each product meets their requirements in all respects before commencing a print run. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In no event shall Sun Chemical be liable for damages of any nature arising out of the use or reliance upon this information. Modifications of the product for reasons of improvements might be made without further notice.