

Constant Current Drivers

350mA LED

- PRI: 220-240V - 50/60Hz
- SEC: 16VDC Max. 0.35A 4W
- ta: -20°C > 75°C

350
MA

IP67

WARRANTY
2
YEAR
WARRANTY



Code: | LED350MA4W

Product Code:	Type:	Max Watts:	Voltage:	Dimensions (mm):	Dimmable:	Power Factor:
LED350MA4W	Constant current	4W max	350mA	39L x 30W x 21D	No	> 0.5

Transformer

Wirewound

Suitable for use with 12V AC LED or Halogen lamps.

- Wirewound transformers suitable for garden lighting, track lighting and live wire systems.
- Auto-resetting internal overload fuse.
- Resin packed for water proofing.
- Supplied with 0.7m 230V cable and 0.7m 12V cable.


12V
AC

IP67

WARRANTY
2
YEAR
WARRANTY



Code: | TH13 / TH 14



If mounting TH series transformers inground DO NOT install with soil packed around transformer. Use a simple water-meter type box with four sides and a lid but no bottom. Test flood the box - water should drain away within 30 mins. If it does not, create adequate free flowing drainage. Not suitable for use in any situation with persistent submersion.

Product Code:	Max Watts:	Voltage:	Dimensions (mm):	Power Factor:	Dimmable:
TH13-50VA	50VA	12V AC	114Ø x 155H	> 0.9	Compatible with PDL-CAT633M dimmer
TH13-100VA	100VA	12V AC	114Ø x 155H	> 0.9	
TH13-150VA	150VA	12V AC	114Ø x 155H	> 0.9	
TH14-200VA	200VA	12V AC	155Ø x 160H	> 0.9	
TH14-300VA	300VA	12V AC	155Ø x 160H	> 0.9	
TH14-400VA	400VA	12V AC	155Ø x 160H	> 0.9	