

DIMMER TESTING WITH: ICDLT13W

DATE: 14.11.19

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	96.6				UNSTABLE
	EM400A3P	PASS	96.6	85.5	6.5	8%	SMOOTH
	EM400TR	PASS	96.6	83.3	10.9	13%	SMOOTH
	EM700TR	PASS	96.6	85.3	13.8	16%	SMOOTH. ONLY DIMS TO 16%
	EM250TR	PASS	96.6	83.4	9	11%	SMOOTH
PDL	PDL354PBDMBW	PASS	96.6	89.3	0	0%	SMOOTH
	PDL354PDMUN	PASS	96.6	85.6	12.9	15%	SMOOTH
	PDL354RDMLD	PASS	96.6	89.6	3.2	4%	SMOOTH
	PDL624M	PASS	96.6	88.8	8.9	10%	SMOOTH
	PDL654M	PASS	96.6	90.3	17.1	19%	SMOOTH. ONLY DIMS TO 19%
KIWI	K005U	PASS	96.6	96.5	0	0%	SMOOTH
GERRARD	MEDM	PASS	96.6	87.2	0	0%	SMOOTH