

DIMMER TESTING WITH: PHDL10WCCT

DATE: 14.11.19

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	221	160	20	13%	UNSTABLE
	EM400A3P	PASS	221	210	18	9%	SMOOTH
	EM400TR	PASS	221	205	25	12%	SMOOTH
	EM700TR	PASS	221	210	37	18%	SMOOTH. ONLY DIMS TO 18%
	EM250TR	PASS	221	207	22	11%	SMOOTH
PDL	PDL354PBDMBW	PASS	221	220	0	0%	SMOOTH
	PDL354PBDMUN	PASS	221	210	33	16%	SMOOTH. ONLY DIMS TO 16%
	PDL354RDMLED	PASS	221	221	7	3%	SMOOTH
	PDL624M	PASS	221	219	20	9%	SMOOTH
	PDL654M	PASS	221	223	43	19%	SMOOTH. ONLY DIMS TO 19%
KIWI	K005U	PASS	221	214	0	0%	SMOOTH
GERRARD	MEDM	PASS	221	219	0	0%	SMOOTH