

DIMMER TESTING WITH: SMDL12W

DATE: 11.3.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	1270	653	45	7%	BAD RANGE
	EM400A3P	PASS	1270	1270	15	1%	SMOOTH
	EM400TR	PASS	1270	1269	40	3%	SMOOTH
	EM700TR	PASS	1270	1266	85	7%	SMOOTH
	EM250TR	PASS	1270	1264	29	2%	SMOOTH
PDL	PDL354PBDMBW	PASS	1270	1262	0	0%	SMOOTH
	PDL354PDMUN	FAIL	1270	264	2	1%	UNSTABLE
	PDL354RDMLED	PASS	1270	1260	0	0%	SMOOTH
	PDL624M	PASS	1270	1260	0	0%	SMOOTH
	PDL654M	PASS	1270	1253	93	7%	SMOOTH
KIWI	K005U	PASS	1270	1253	2	0%	SMOOTH
GERRARD	MEDM	PASS	1270	1254	0	0%	SMOOTH