

DIMMER TESTING WITH: SMDL7W

DATE: 11.3.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	996	975	168	17%	UNSTABLE
	EM400A3P	PASS	996	996	107	11%	SMOOTH
	EM400TR	PASS	996	992	182	18%	SMOOTH. ONLY DIMS TO 18%
	EM700TR	FAIL	996	980	290	30%	BAD RANGE
	EM250TR	PASS	996	996	145	15%	SMOOTH
PDL	PDL354PBDMBW	PASS	996	999	15	2%	SMOOTH
	PDL354PDMUN	PASS	996	980	0	0%	SMOOTH
	PDL354RDMLD	PASS	996	992	21	2%	SMOOTH
	PDL624M	PASS	996	973	0	0%	SMOOTH
	PDL654M	FAIL	996	983	330	34%	BAD RANGE
KIWI	K005U	PASS	996	983	0	0%	SMOOTH
GERRARD	MEDM	PASS	996	993	0	0%	SMOOTH