

DIMMER TESTING WITH: SMT23

DATE: 19.5.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	1920	1230	223	18%	POOR RANGE
	EM400A3P	PASS	1920	1776	54	3%	SMOOTH
	EM400TR	PASS	1920	1772	189	11%	SMOOTH
	EM700TR	PASS	1920	1785	227	13%	SMOOTH
	EM250TR	PASS	1920	1770	157	9%	SMOOTH
PDL	PDL354PBDMBW	PASS	1920	1813	0	0%	SMOOTH
	PDL354PBDMUN	PASS	1920	1807	231	13%	SMOOTH
	PDL354RDMLED	PASS	1920	1826	43	2%	SMOOTH
	PDL624M	PASS	1920	1821	155	9%	SMOOTH
	PDL654M	PASS	1920	1843	313	17%	SMOOTH. ONLY DIMS TO 17%
KIWI	K005U	PASS	1920	1867	0	0%	SMOOTH
GERRARD	MEDM	PASS	1920	1820	0	0%	SMOOTH