

DIMMER TESTING WITH: SMT81

DATE: 19.5.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	PASS	1850	1377	255	19%	SMOOTH. ONLY DIMS TO 19%
	EM400A3P	PASS	1850	1785	55	3%	SMOOTH.
	EM400TR	PASS	1850	1760	212	12%	SMOOTH.
	EM700TR	PASS	1850	1767	254	14%	SMOOTH.
	EM250TR	PASS	1850	1746	173	10%	SMOOTH.
PDL	PDL354PBDMBW	PASS	1850	1773	0	0%	SMOOTH.
	PDL354PBDMUN	PASS	1850	1768	230	13%	SMOOTH.
	PDL354RDMLD	PASS	1850	1775	69	4%	SMOOTH.
	PDL624M	PASS	1850	1691	165	10%	SMOOTH.
	PDL654M	PASS	1850	1718	34.5	2%	SMOOTH.
KIWI	K005U	PASS	1850	1810	0	0%	SMOOTH.
GERRARD	MEDM	PASS	1850	1765	0	0%	SMOOTH.