DIMMER TESTING WITH: KARLIND

25/05/2022

| DIMMER BRAND | DIMMER MODEL | PASS/FAIL | | MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100% | - | % WHEN DIMMER ON MINIMUM SETTING | COMMENTS |
|--------------|--------------|-----------|------|--|----|-------------------------------------|-------------|
| HPM LEGRAND | EM400A2P | FAIL | 1178 | 577 | 51 | 9% | poor range |
| | EM400TR | PASS | 1178 | 1141 | 41 | 4% | smooth |
| | EM700TR | PASS | 1178 | 1157 | 56 | 5% | smooth |
| | EM250TR | PASS | 1178 | 1130 | 33 | 3% | smooth |
| PDL | PDL354PBDMBW | PASS | 1178 | 1180 | 2 | 0% | very smooth |
| | PDL354PBDMUN | PASS | 1178 | 1167 | 51 | 4% | smooth |
| | PDL354RDMLED | PASS | 1178 | 1179 | 3 | 0% | very smooth |
| | PDL624tM | PASS | 1178 | 1178 | 27 | 2% | smooth |
| | PDL654M | PASS | 1178 | 1181 | 96 | 8% | smooth |
| KIWI | K005U | PASS | 1178 | 1185 | 0 | 0% | very smooth |
| GERRARD | MEDM | PASS | 1178 | 1185 | 0 | 0% | very smooth |
| • | | | | | • | | |