

DIMMER TESTING WITH: LEDB22SLIM

DATE: 28.4.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	30				UNSTABLE
	EM400A3P	PASS	30	25	0	0%	SMOOTH
	EM400TR	PASS	30	25	4	16%	SMOOTH. ONLY DIMS TO 16%
	EM700TR	PASS	30	25	6	24%	SMOOTH. ONLY DIMS TO 24%
	EM250TR	PASS	30	25	4	16%	SMOOTH. ONLY DIMS TO 16%
PDL	PDL354PBDMBW	PASS	30	27	0	0%	SMOOTH
	PDL354PDMUN	PASS	30	27	4	15%	SMOOTH
	PDL354RDMLED	PASS	30	28	1	4%	SMOOTH
	PDL624M	PASS	30	26	0	0%	SMOOTH
	PDL654M	PASS	30	27	7	26%	SMOOTH. ONLY DIMS TO 26%
KIWI	K005U	PASS	30	27	0	0%	SMOOTH
GERRARD	MEDM	PASS	30	27	0	0%	SMOOTH