

DIMMER TESTING WITH: WP387S

DATE: 21.7.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	371	298	65	22%	POOR RANGE
	EM400A3P	PASS	371	368	13	4%	SMOOTH
	EM400TR	PASS	371	368	52	14%	SMOOTH
	EM700TR	PASS	371	368	65	18%	SMOOTH. ONLY DIMS TO 18%
	EM250TR	PASS	371	368	42	11%	SMOOTH
PDL	PDL354PBDMBW	PASS	371	370	5	1%	SMOOTH
	PDL354PBDMUN	FAIL	371	368	61	17%	UNSTABLE
	PDL354RDMLED	PASS	371	370	10	3%	SMOOTH
	PDL624M	PASS	371	370	39	11%	SMOOTH
	PDL654M	PASS	371	370	107	29%	SMOOTH. ONLY DIMS TO 29%
KIWI	K005U	PASS	371	370	0	0%	SMOOTH
GERRARD	MEDM	PASS	371	370	0	0%	SMOOTH

DIMMER TESTING WITH: WP387L

DATE: 29.11.19

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	PASS	398	357	70	20%	SMOOTH. ONLY DIMS TO 20%
	EM400A3P	PASS	398	398	34	9%	SMOOTH
	EM400TR	PASS	398	398	58	15%	SMOOTH. ONLY DIMS TO 15%
	EM700TR	PASS	398	398	78	20%	SMOOTH. ONLY DIMS TO 20%
	EM250TR	PASS	398	398	45	11%	SMOOTH
PDL	PDL354PBDMBW	PASS	398	399	2	1%	SMOOTH
	PDL354PBDMUN	PASS	398	398	68	17%	SMOOTH. ONLY DIMS TO 17%
	PDL354RDMLED	PASS	398	399	3	1%	SMOOTH
	PDL624M	PASS	398	398	39	10%	SMOOTH
	PDL654M	PASS	398	398	127	32%	SMOOTH. ONLY DIMS TO 32%
KIWI	K005U	PASS	398	398	0	0%	SMOOTH
GERRARD	MEDM	PASS	398	398	0	0%	SMOOTH