

DIMMER TESTING WITH: DECOG200

DATE: 18.3.20

DIMMER BRAND	DIMMER MODEL	PASS/FAIL	MAX LUX WITH NO DIMMER IN CIRCUIT	MAX LUX LEVEL WITH DIMMER IN CIRCUIT 100%	MIN LUX WITH DIMMER	% WHEN DIMMER ON MINIMUM SETTING	COMMENTS
HPM LEGRAND	EM400A2P	FAIL	13.7	7.6	0	0%	UNSTABLE
	EM400A3P	PASS	13.7	13.7	0	0%	SMOOTH
	EM400TR	PASS	13.7	13.2	0	0%	SMOOTH
	EM700TR	FAIL	13.7	13.4	2	15%	POOR RANGE
	EM250TR	PASS	13.7	13.4	0	0%	SMOOTH
PDL	PDL354PBDMBW	PASS	13.7	13.7	0	0%	SMOOTH
	PDL354PBDMUN	FAIL	13.7	8.7	6	69%	POOR RANGE
	PDL354RDMLD	PASS	13.7	13.7	0	0%	SMOOTH
	PDL624M	PASS	13.7	11.7	0	0%	SMOOTH
	PDL654M	PASS	13.7	13.7	0	0%	SMOOTH
KIWI	K005U	PASS	13.7	6.8	0	0%	SMOOTH
GERRARD	MEDM	PASS	13.7	13.1	0	0%	SMOOTH