
# **Allure Downlights**

# **A503 - CRI80 - TRICOLOUR TEMPERATURE**

**Product Codes: NRLG10WCCT-WB** 





















- 10W No Rim Low Glare Recessed Downlight
- Dimmable, with compatible dimmer
- Low Glare design
- Tricolour suitable
- Suitable for residential or commercial in interior installations.
- Lifespan 54,000 hours(L70)
- Removable driver

#### **Materials & Finish**

- Material
  - Aluminium
  - Lens Opaque PMMA diffuser (deep recess lens, reduces unwwanted glare)
- LED Type
  - Integrated SMD LED
- Shape
  - Round
- Colour
  - White with Black reflector

## **Specifications**

- Switching Capacity 30,000
- Triac Dimmable
- Rating IC-F/IC-4
- Power
  - Voltage 230V
  - Driver coverable driver
  - -Power Factor > 0.9
  - -Wattage 10W(including the driver)
  - -Max ambient operating temperature: +45°C
- Light Output
  - -Lumens 600lm (3000K) | 680lm (4000K) | 630lm (6500K)
  - -Colour Temperature 3000K | 4000K | 6500K
  - -CRI >80

### Installation

- Mounting Recessed
- \*HCB: 0mm | \*SCB: 0mm | Height of fitting: 75mm

#### Note:

\*HCB(Height Clearance to Building) and SCB(Side Clearance to Building) clearances of 0mm does not mean that you can drill a hole in solid concrete or wood and install downlight. You must always allow for heat dissipation. Do not install closer than 500mm to illuminated surface. Please refer to instruction sheet for more details.