



Product Features

- 3 x Colour Temperature Selectable
- 3 x Wattage Selectable
- Replaceable Surge Protection Device (SPD) 10kV
- 2m cord, with NZ plug

Materials & Finish

- Material
- Die-Casting Aluminium with PC lens



Specifications

- Voltage 230V
- IP Rating IP65
- IKRating IK08
- Lamp Technology LED
- Beam angle 90° with PC Lens
- Lamp Life: L70 50,000
- CCT Switchable 4000K | 5000K | 6000K
- Lumen efficacy 170lm/w (+/-5%)
- refer to photometric files for lumens per colour temp/wattage
- Wattage Selectable 200W | 160W | 120W
- SPD specification:10kV, full specification supplied on request.
- Weight: 2.7KG (3.2kg with diffuser)
- 2m cord supplied with NZ plug fitted.
- Ambient temperature range: -20°C- 40°C

Installation

• Mounting -Surface Mounted Suspended

Accessories available:

- Sensor (PLUTOSENSOR) sold separately
- Sensor Remote (PLUTOREMOTE) sold separately
- Diffuser (PLUTODIFFUSER) sold separately

*We recommend at least 1x remote per 20 high bays.

Eurotech Lighting 11 Westward Ho Road, Glen Eden, Auckland, New Zealand