

YYR220, previous name YYR15

CCT select LED Button



The YYR Ceiling Button range offers a cost-effective, tamper-resistant lighting solution, available in three sizes (280mm, 330mm, 400mm*) from durable ABS polycarbonate, each luminaire features tri-wattage selection, triac dimmable, and CCT selectability for easy on-site colour adjustment. Installation is quick with centralised cabling and a simple fit bracket. *Other options within range are wattage & selectable. YYR220 is CCT selectable only

General

Product Codes

YYR220 220mm diameter

Other codes in the range:

YYR280CCT 280mm diameter

YYR330CCT 330mm diameter

YYR400CCT 400mm diameter

Weight

800gms

Mounting Options

Surface

Dimensions

mm = 53H x 220D

Finish Options

Material: PC Housing, PC Diffuser

Body Colour: White

Environment

IP54

Electrical

Ambient Operating Temperature

(-25° ~ +45°)

Voltage

230V

Class

Class II (double insulated)

Power Consumption

15W

Luminous Efficacy

90 lm/W (+/- 5%)

Lumen Maintenance

30,000 hours (L70) Ta 25°

Dimming Options

Triac Dimmable

Photometrics

Flux (Lumens) - (+/- 5%)

3000K 1349

4000K 1549

6000K 1413

Optics

Opal

Beam Angle

115°

Light Source

Integrated SMD LED

Correlated Colour Temperature

3000K or 4000K or 6000K

(CCT Selectable)


Colour Rendering Index (CRI)

CRI >80


Product Image




Product Illustration



Light Distribution @ 4k



Colour Quality Scale



All product specification are correct at the time of printing, and are subject to change without notice.



Version: 2.1

Date: 11.2025

T: 0800 OUT A BX (688229) | W eurotechlighting.co.nz | E info@eurotechlighting.co.nz