

JF UV Series Product Overview



Jarvis Lighting® JF UV Series LED Flood Light Luminaire

The Jarvis JF Series slim LED flood light is a cost-effective solution for a wide variety of flood lighting applications. Featuring high quality and long lasting LEDs this fixture is available in 4 different mounting options.

KEY FEATURES:

- Slim die-cast aluminum housing with durable powder coat finish
- Optics NEMA Type 7Hx6V
- 10 Year Warranty

JF-TR
Trunnion
Mount



JF-SFM
Slipfitter
Mount



JF-2L/3L/5L/7L - KM default mounting option
JF-8L/13L/18L/26L - SFM default mounting option

Most Popular Models and Specifications:

CATALOG #	DESCRIPTION	DLC MODEL #	INPUT	POWER	LUMENS	CCT	CRI	PF
JF-2L-50K-BRZ-[KM or TR]	Flood Light available in either Knuckle Mount (KM) or Trunnion Mount (TR)	MFD0815W27V50KDB76[KN,TR]	120-277V 50/60Hz	15W	2,000 lm	5000K	≥ 70	≥ 0.9
JF-3L-50K-BRZ-[KM or TR]	Flood Light available in either Knuckle Mount (KM) or Trunnion Mount (TR)	MFD0827W27V50KDB76[KN,TR]	120-277V 50/60Hz	27W	3,600 lm	5000K	≥ 70	≥ 0.9
JF-5L-50K-BRZ-[KM or TR]	Flood Light available in either Knuckle Mount (KM) or Trunnion Mount (TR)	MFD0845W27V50KDB76[KN,TR]	120-277V 50/60Hz	45W	5,650 lm	5000K	≥ 70	≥ 0.9
JF-7L-50K-BRZ-[KM or TR]	Flood Light available in either Knuckle Mount (KM) or Trunnion Mount (TR)	MFD0860W27V50KDB76[KN,TR]	120-277V 50/60Hz	60W	7,450 lm	5000K	≥ 70	≥ 0.9
JF-8L-50K-BRZ-[SFM or YK]	Flood Light available in either Slipfitter Mount (SFM) or Yoke Mount (YK)	MFD0870W27V50KDB76[YK,SP]	120-277V 50/60Hz	70W	8,900 lm	5000K	≥ 70	≥ 0.9
JF-13L-50K-BRZ-[SFM or YK]	Flood Light available in either Slipfitter Mount (SFM) or Yoke Mount (YK)	MFD08100W27V50KDB76[YK,SP]	120-277V 50/60Hz	100W	13,300 lm	5000K	≥ 70	≥ 0.9
JF-18L-50K-BRZ-[SFM or YK]	Flood Light available in either Slipfitter Mount (SFM) or Yoke Mount (YK)	MFD08135W27V50KDB76[YK,SP]	120-277V 50/60Hz	135W	18,000 lm	5000K	≥ 70	≥ 0.9
JF-26L-50K-BRZ-[SFM or YK]	Flood Light available in either Slipfitter Mount (SFM) or Yoke Mount (YK)	MFD08200W27V50KDB76[YK,SP]	120-277V 50/60Hz	200W	26,200 lm	5000K	≥ 70	≥ 0.9

Additional variants and models may be available. Models for 347-480V sites are available, see the technical spec sheet for catalog numbers.

Full technical specifications available. See "JF Series Technical Specification Sheet" or contact a Jarvis representative for more information.



DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

UL Listed to UL 1598 and UL 8750. Rated for Wet Locations.