

LSL2 Series Product Overview



LSL2 Series LED Linear Strip Luminaire

This sleek linear strip fixture has a 120° beam angle and is the perfect solution for low bay lighting applications

KEY FEATURES:

- Sleek, linear fixture
- Designed to easily replace HID and fluorescent fixtures
- Durable aluminum housing and polycarbonate lens
- Suitable for suspended mounting
- 0-10V dimming
- Additional color temperatures are available upon request
- 10 Year Warranty



Most Popular Models and Specifications:

| Catalog # | Description | DLC Product ID | Input | Power | Lumens | CCT | CRI | PF |
|------------------------|--------------------------------------|----------------|------------------|-------|----------|-------------------|------|-------|
| LSL2-4-24W-50K | 4' Linear Strip Light | P6DYM1ND | 100-277V 50/60Hz | 24W | 3,120 lm | 5000K | ≥ 80 | ≥ 0.9 |
| LSL2-4-40W-30K/40K/50K | 4' Adjustable CCT Linear Strip Light | PQZORRKA | 100-277V 50/60Hz | 40W | 5,200 lm | 3000K/4000K/5000K | ≥ 80 | ≥ 0.9 |
| LSL2-4-40W-50K | 4' Linear Strip Light | PGQH3FR | 100-277V 50/60Hz | 40W | 5,200 lm | 5000K | ≥ 80 | ≥ 0.9 |
| LSL2-8-64W-40K | 8' Linear Strip Light | PNY1N76J | 100-277V 50/60Hz | 64W | 8,525 lm | 4000K | ≥ 80 | ≥ 0.9 |
| LSL2-8-8L-40K | 8' Linear Strip Light | In Progress | 100-277V 50/60Hz | 64W | 8,320 lm | 4000K | ≥ 80 | ≥ 0.9 |
| LSL2-8-8L-50K | 8' Linear Strip Light | In Progress | 100-277V 50/60Hz | 64W | 8,320 lm | 5000K | ≥ 80 | ≥ 0.9 |

Models in additional CCT color temperatures are available, see the technical spec sheet for catalog numbers.

Full technical specifications available. See "LSL2 Series Technical Specification Sheet" or contact a Jarvis representative for more information.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified. UL Listed to UL 1598 and UL 8750.