



Long leg option dimensions

Short leg option
dimensions:
A - 560mm
B - 430mm

Bolt on log store shown with short leg option stove



| Declaration of Performance | | Solid fuel | Wood |
|---|-------|------------|------|
| Test duration | h | 1.03 | 0.81 |
| Total efficiency | % | 75.7 | 81.2 |
| Nominal heat output | kW | 5.0 | 5.0 |
| Mean CO emission (at 13% O ₂) | % | 0.06 | 0.10 |
| Mean flue gas temperature | °C | 326 | 247 |
| Flue gas mass flow | g/s | 4.4 | 4.3 |
| Mean OGC (at 13% O ₂) | Nmg/m | 4 | 72 |
| Mean NO _x (at 13% O ₂) | Nmg/m | 100 | 84 |
| DIN Plus dust (at 13% O ₂) | Nmg/m | 8 | 25 |
| Hearth temperature | °C | 66 | 66 |
| Combustibles - side | mm | 450 | 450 |
| Combustibles - rear | mm | 350 | 350 |
| Non combustibles - rear | mm | 50 | 50 |
| Non combustibles - side | mm | 75 | 75 |

Warranty 10 years, exclusions apply. Manufactured by Dunsley Heat Ltd, Bridge Mills, Holmfirth, Yorkshire, England



FS610184

DB-AV-22/08/19