

General Specifications	
Power requirements	220-240 V, 50/60 Hz
Energy consumption *	1: 20, 2: 36, 3: 54, 4: 74, 5: 105, 6: 135 Watt; Standby: <1 Watt
Dimensions (without / with packaging)	H 61 x W 38 x D 41 cm / carton: H 74 x W 43 x D 45 cm
Weight (without / with packaging)	13 kg / 17 kg
Air delivery (incl. filters) *	1: 50, 2: 80, 3: 140, 4: 200, 5: 260, 6: 350 m ³ /h
Sound pressure/power level **	L _p 1: 22, 2: 33, 3: 41, 4: 47, 5: 52, 6: 57 dB(A); L _w 1: 32, 2: 43, 3: 51, 4: 57, 5: 62, 6: 67 dB(A)
Fan motor	centrifugal, backward curved, with thermal protector, non-stop use approved
Control panel	4-key touch-pad with 16 character 2-line LCD display
Air intake	dual arches at base of unit
Air outlet	320° EvenFlow™ diffuser
Colour of main housing / locking arms	light grey / white
Housing material	non off-gassing, impact-resistant, UV-stabilized ABS
Performance	
Total system efficiency (certified)	≥ 99.97% for particles ≥ 0.3 µm (individually tested at highest fan speed)
Air delivery (certified)	yes (individually tested with all filters fitted)
Leak tested	yes
Classification acc. to EN 1822-5: 2009	HEPA class H13 (MPPS efficiency: ≥ 99.95% @ 0.19 µm at airflow rate ≤ 240 m ³ /h) HEPA class H12 (MPPS efficiency: ≥ 99.50% @ 0.14 µm at airflow rate ≤ 560 m ³ /h)
Filter Configuration	
Pre- & Gas-filter	<p>PreMax™ MG Filter F8MG (S)</p> <p>Pre-Filter Stage:</p> <p>Purpose: control of coarse and fine particulate matter; protection of subsequent filters</p> <p>Media: non-woven glass microfiber, mini-pleated for high-capacity</p> <p>Efficiency: ≥ 55% at ≥ 0.3 µm (class F8)</p> <p>Surface area: approx. 1.9 m²</p> <p>Gas- & Odour Filter Stage:</p> <p>Purpose: control of a wide range of chemical contaminants and odours</p> <p>Media: MultiGas™ activated carbon & impregnated activated alumina (AC/4 + IA/4)</p> <p>Weight: approx. 1.0 kg</p>
HEPA-filter	<p>HyperHEPA® Filter H12/13 (L)</p> <p>Purpose: control of fine & ultra-fine particulate matter</p> <p>Media: non-woven glass microfiber, hospital-grade HyperHEPA® filter</p> <p>Efficiency: ≥ 99.97% at ≥ 0.3 µm (class H12/13)</p> <p>Surface area: approx. 5.0 m²</p>
Features	
Display languages	4 user-selectable languages: English, French, German, Italian (or Spanish)
Fan speed settings	6
Intelligent filter life monitor	yes (monitors actual usage of each individual filter)
Filter life status LEDs	2
Advanced timer	yes (allows programming of operating hours and weekdays)
Advanced fan speed selection	yes (allows programming of different fan speeds for 2 different time periods)
Adjustable filter load indices	3 (large dust, chemicals and fine dust)
Supplied accessories	remote control (incl. battery), power cord with plug, casters, certificate of performance
Optional accessories	VMF wall-mount bracket, PF40 coarse dust pre-filter, InFlow , VM InFlow & OutFlow duct connections, FlexVac & VM FlexVac mobile & wall-mounted source capture kits.
Electrical safety certification	IEC/IECEE (CB-Scheme), CE, SEV, KTL, EAC

* per fan speed measured at 230V, 50Hz; tolerance ± 10% (± 10 m³/h); ** tolerance: ± 3 dB(A); All technical specifications are subject to change without prior notice.