



Noodoe EV DC360P

Smart EV Charging

SPECIFICATIONS

Cloud service	Noodoe EV OS
Maximum output power	360 kW
Output power	CCS1: 500 A @150~720 Vdc or 380 A @950 Vdc CHAdeMO: 200 A @150~500 Vdc
Vehicle connector	CCS1, CHAdeMO
Charging cable length	13 feet / 4 m
Input power	Power Cabinet: 3-phase, 5-wire, 480 Vac, 561 A maximum Power Dispenser: 1-phase, 3-wire, 200~240 Vac, 10 A maximum
Grounding system	TN, TT, IT
Efficiency	> 94%
Power factor	> 0.99
Display	7 inch LCD
Communication protocol	OCPP 1.6 JSON
Vehicle communication interface	ISO 15118
Network connectivity	Ethernet, Wi-Fi, 4G
RFID	RFID ISO/IEC 14443 A/B
NEMA enclosures(NEMA)	NEMA 3R
Impact protection	IK10
Electrical protection	Over voltage protection, over current protection, over power protection, over temperature protection, under voltage protection, residual current device, surge protection, short circuit protction, insulation monitoring device
Operating temperature	-22 °F to +122 °F / -30 °C to +50 °C
Dimensions	Power Cabinet: 55.1 (W) x 74.8 (H) x 31.5 (D) in / 1400 (W) x 1900 (H) x 800 (D) mm Power Dispenser: 27.6 (W) x 70.9 (H) x 21.7 (D) in / 700 (W) x 1800 (H) x 550 (D) mm
Weight	Power Cabinet: 2646 lbs / 1200 kg Power Dispenser: 661 lbs / 300 kg
Certifications	ETL, FCC

Noodoe EV OS



Noodoe Inc.
9896 Bissonnet,
Suite 440
Houston, TX 7703,
United States
+1 281-888-3429
info@noodoe.com
noodoe.com


Width
55.1 in /
1400 mm

Depth
31.5 in /
800 mm


Width
27.6 in /
700 mm

Depth
21.7 in /
550 mm

Height
74.8 in /
1900 mm



Height
70.9 in /
1800 mm



COMBINATION

1 Cabinet + 1 Dispenser



1 Cabinet + 2 Dispensers

