

Page 1/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

# **SECTION 1:** Identification of the substance/mixture and of the company/undertaking

#### -1.1 Product identifier

- Trade name: <u>EXTREME BLACK</u>
- UFI: R8F0-Y069-000T-FDPG
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Life cycle stages PW Widespread use by professional workers
- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC31 Polishes and wax blends
- Application of the substance / the mixture Wetting agent
- Uses advised against

The mixture is not raccomended for industrial, professional and consumer applications not specified as relevant identified uses

#### - 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

MA-FRA S.p.A. a Socio Unico Via Aquileia, 44/46 20021 Baranzate (MI) ITALIA Tel.+39 023569981 www.mafra.com mafra@mafra.it

#### - Informing department: E-mail: lab@mafra.it

info@mafra.it

- 1.4 Emergency telephone number: In case of accident call the emergency number 112

# **SECTION 2: Hazards identification**

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2

H225 Highly flammable liquid and vapour.



nazara

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.

2 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2H315 Causes skin irritation.STOT SE 3H336 May cause drowsiness or dizziness.

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

#### Trade name: EXTREME BLACK

	(Contd. of page 1)
2.2 Label eleme	nts
Labelling accord	ding to Regulation (EC) No 1272/2008
	lassified and labelled according to the GB CLP regulation.
Hazard pictogra	
GHS02 GHS	07 GHS08 GHS09
Signal word Dat	nger
	ning components of labelling:
Hydrocarbons, (	
Hazard statemen	nts
H225 Highly flat	mmable liquid and vapour.
H315 Causes ski	in irritation.
H336 May cause	e drowsiness or dizziness.
H304 May be fai	tal if swallowed and enters airways.
	quatic life with long lasting effects.
Precautionary s	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P303+P361+P3	53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or
	shower].
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulation
2.3 Other hazar	ds
Results of PBT	and vPvB assessment
PBT: Not applic	
vPvB: Not appli	cable.
<b>H H D H H H H H H H H H H</b>	

#### - 3.2 Mixtures

- Description: Mixture of substances

#### - Dangerous components:

Dungerous components.		
CAS: 64742-49-0	Hydrocarbons, C6, isoalkanes	70-100%
EINECS: 265-151-9	🚸 Flam. Liq. 2, H225; 🚸 Asp. Tox. 1, H304; 🔖 Aquatic Chronic 2, H411;	
Reg.nr.: 012119484651-34 <	🚯 Skin Irrit. 2, H315; STOT SE 3, H336	
- Additional information For the wording of the listed hazard phrases refer to section 16		

Additional information For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- -4.1 Description of first aid measures
- General information
- Take affected persons into the open air.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation

In case of unconsciousness bring patient into stable side position for transport. Supply fresh air; consult doctor in case of symptoms. Call a doctor immediately.

(Contd. on page 3)

GB

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

(Contd. of page 2)

#### Trade name: EXTREME BLACK

- Supply fresh air.
- *After skin contact* Instantly wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- After eye contact Rinse opened eye for several minutes under running water.
- After swallowing Call a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed Dazed
  - Unconsciousness
- 4.3 Indication of any immediate medical attention and special treatment needed If swallowed, gastric irrigation Medical supervision for at least 48 hours
- **SECTION 5: Firefighting measures**
- 5.1 Extinguishing media
   Suitable extinguishing agents CO2. Do not use water. Use fire fighting measures that suit the environment.
  - For safety reasons unsuitable extinguishing agents
- Water. Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. Can be released in case of fire Carbon monoxide (CO)
- 5.3 Advice for firefighters
- Protective equipment: Do not inhale explosion gases or combustion gases. Protection means for respiratory tract
   Additional information
- Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Keep people at a distance and stay on the windward side. Bring persons out of danger. Keep away from ignition sources Protective gloves. (EN 374) - For non-emergency personnel Ensure adequate ventilation Keep away from ignition sources Wear protective clothing. - For emergency responders PVC gloves Nitrile rubber, NBR - 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system. Do not allow to enter drainage system, surface or ground water. - 6.3 Methods and material for containment and cleaning up: *Ensure adequate ventilation.* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents Dispose of the material collected according to regulations. (Contd. on page 4)

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

(Contd. of page 3)

#### Trade name: EXTREME BLACK

#### - 6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

# **SECTION 7: Handling and storage**

## - 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Take off immediately all contaminated clothing Wash hands during breaks and at the end of the work. Do not eat, drink or smoke while working.

- Information about protection against explosions and fires: Highly volatile, flammable constituents are released during processing. Do not spray on flames or red-hot objects. Keep ignition sources away - Do not smoke. Protect from heat. Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage
- Requirements to be met by storerooms and containers: Store in cool location. Store only in the original container.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed containers.

- Class according to regulation on inflammable liquids: A I

- 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- DNELs

64742-49-0 Hydrocarbons, C6, isoalkanes			
		1,301 mg/Kg bw/day (Consumers)	
Dermal	Systemic long-term effects	13,964 mg/Kg bw/day (Industrial Workers)	
		1,377 mg/Kg bw/day (Consumers)	
Inhalative	Systemic long-term effects	5,306 mg/m <sup>3</sup> (Industrial Workers)	
		1,137 mg/m <sup>3</sup> (Consumers)	

- Additional information: The lists that were valid during the compilation were used as basis.

#### - 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Breathing equipment: Not necessary if room is well-ventilated.

<sup>- 8.1</sup> Control parameters

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

(Contd. of page 4)

#### Trade name: EXTREME BLACK

#### - Hand protection



Protective gloves. (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves PVC gloves

Nitrile rubber, NBR

- Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 15 minutes (Permeation according to EN 16523-1:2015: Level 1).

- Eye/face protection



Tightly sealed safety glasses.

- Environmental exposure controls Disposal must be made according to official regulations.

## **SECTION 9: Physical and chemical properties**

- General Information       - Finite         - Physical state       Fluid         - Colour:       Red         - Odour threshold:       Not determined.         - Melting point or initial boiling point and boiling range       138 °C         - Flammability       Highly flammable.         - Lower and upper explosion limit       138 °C         - Vower and upper explosion limit       13 °C         - Jower and upper explosion limit       10 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)         - Upper:       10 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)         - Jupper:       10 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)         - Boeiling noint:       10 °C         - Ignition temperature:       Not determined.         - Decomposition temperature:       Not determined.         - PH       Mixture is non-soluble (in water).         - Viscosity:       .         - Kinematic viscosity       Not determined.         - Solubility       .         - Partition coefficient n-octanol/water (log value)       Not determined.         - Vapour pressure at 20 °C:       3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)         - Density and/or relative density       .         - Density and/or relative density       .         - Density and/or relat	- 9.1 Information on basic physical and chemical propert	ies
Physical stateFluid- Colour:Red- Odour:Characteristic- Odour threshold:Not determined Melting point/freezing point:Not determined Melting point/freezing point:Not determined- Boiling point or initial boiling point and boiling range138 °C- FlammabilityHighly flammable Lower and upper explosion limit Lower:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Upper:10 °C- Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Pbecomposition temperature:Not determined PHMixture is non-soluble (in water) Viscosity: SolubilityNot determined Watter:Not determined SolubilityNot determined Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined Vapour densityNot determined Vapour densityNot determined Partition coefficient n-octanol/water (log value)Not determined Partition coefficient n-octanol/water (log value)Not determined Papur densityNot determined Papur densityNot determined Papur densityNot determined Papur density <t< th=""><th></th><th></th></t<>		
Odour:Characteristic•Odour threshold:Not determined.• Melting point/freezing point:Not determined.• Melting point/freezing point:Not determined.• Boiling point or initial boiling point and boiling range138 °C• FlammabilityHighly flammable.• Lower and upper explosion limit1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)• Upper:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)• Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)• Flash point:10 °C• Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)• Decomposition temperature:Not determined.• JuptNot determined.• JuptNot determined.• Viscosity:Not determined.• Viscosity:Not determined.• Viscosity:Not determined.• Vapamic:Not miscible or difficult to mix• Appaur pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)• Density and/or relative densityNot determined.• Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)• Density at 20 °C0.73 g/cm³• Relative densityNot determined.• Vapour densityNot determined.• Partition coefficient n-octanol/water (log value)Not determined.• Papearance:-• Papearance:-• Papearance:-• Form:Fluid		Fluid
Odour threshold:Not determined.Melting point/freezing point:Not determinedBoiling point or initial boiling point and boiling range138 °CFlammabilityHighly flammable.Lower and upper explosion limit13 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)Upper:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)Flash point:10 °CIgnition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)Decomposition temperature:Not determined PHMixture is non-soluble (in water) Viscosity:Not determined SolubilityNot determined SolubilityNot determined Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density at 20 °C0.73 g/cm³- Relative densityNot determined Japarance: Japarance: Form:Fluid	- Colour:	Red
Melting point/freezing point:Not determinedBoiling point or initial boiling point and boiling range138 °CFlammabilityHighly flammable.Lower and upper explosion limit1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)Upper:1.0 VOL % (64742-49-0 Hydrocarbons, C6, isoalkanes)Flash point:10 °CIgnition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)Decomposition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)PHNot determinedPHMixture is non-soluble (in water).Viscosity:Not determineddynamic:Not determinedSolubilityNot determinedWater:Not determinedVapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)-Density and/or relative densityNot determinedVapour densityNot determinedVapour densityNot determinedVapour densityNot determinedVapour densityNot determinedVapour densityNot determined9.2 Other information-9.2 Other information-9.2 Other informationFluid	- Odour:	Characteristic
Boiling point or initial boiling point and boiling range138 °C- FlammabilityHighly flammable Lower and upper explosion limit Lower:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Flash point:10 °C- Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:Not determined PHMixture is non-soluble (in water) Viscosity: Kinematic viscosityNot determined dynamic:Not determined SolubilityNot determined Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative densityNot determined Vapour densityNot determined Solubility Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined 9.2 Other information Appearance: Form:Fluid	- Odour threshold:	Not determined.
Boiling point or initial boiling point and boiling range138 °C- FlammabilityHighly flammable Lower and upper explosion limit Lower:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Flash point:10 °C- Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:Not determined PHMixture is non-soluble (in water) Viscosity: Kinematic viscosityNot determined dynamic:Not determined SolubilityNot determined Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative densityNot determined Vapour densityNot determined Solubility Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined 9.2 Other information Appearance: Form:Fluid	- Melting point/freezing point:	Not determined
- Lower and upper explosion limit- Lower:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Flash point:10 °C- Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Viscosity:- Kinematic viscosity- Kinematic viscosity- Aynamic:- Solubility- Water:- Water:- Vapour pressure at 20 °C:- Density and/or relative density- Density at 20 °C- Relative density- Not determined Vapour density- Soluber information- Appearance:- Form:- Form:	- Boiling point or initial boiling point and boiling range	138 °C
- Lower:1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)• Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)• Flash point:10 °C• Jgnition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)• Decomposition temperature:Not determined.• PHMixture is non-soluble (in water).• Viscosity:Not determined.• Aynamic:Not determined.• SolubilityNot determined.• Partition coefficient n-octanol/water (log value)Not determined.• Vapour pressure at 20 °C:0.73 g/cm³• Density and/or relative densityNot determined.• Vapour densityNot determined.• Vapour densityNot determined.• Jons to 20 °C0.73 g/cm³• Relative densityNot determined.• Partinon coefficientNot determined.• Density and/or relative densityNot determined.• Density and/or relative densityNot determined.• Partition coefficient n-octanol/water (log value)Not determined.• Density and/or relative densityNot determined.• Density and/or relative densityNot determined.• Density and/or relative densityNot determined.• Paperance:-• Paperance:-• Form:Fluid	- Flammability	Highly flammable.
- Upper:10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)- Flash point:10 °C- Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:Not determined pHMixture is non-soluble (in water) Viscosity:- Kinematic viscosityNot determined dynamic:Not determined SolubilityNot determined Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative densityNot determined Vapour densityNot determined Vapour densityNot determined Vapour densityNot determined Parsition coefficient n-octanol/water (log value)Not determined Density and/or relative density0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined SolubilityNot determined Form:Fluid	- Lower and upper explosion limit	
- Flash point:10 °C- Ignition temperature:405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)- Decomposition temperature:Not determined pHMixture is non-soluble (in water) Viscosity:Not determined dynamic:Not determined SolubilityNot determined Water:Not miscible or difficult to mix- Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined Jonne formation- 9.2 Other information- Appearance:- Form:Fluid	-Lower:	1.3 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)
<ul> <li>Ignition temperature:</li> <li>Ignition temperature:</li> <li>Decomposition temperature:</li> <li>Not determined.</li> <li>PH</li> <li>Viscosity:</li> <li>Kinematic viscosity</li> <li>Not determined.</li> <li>Vot determined.</li> <li>Vot determined.</li> <li>Not determined.</li> <li>Solubility</li> <li>Water:</li> <li>Not miscible or difficult to mix</li> <li>Partition coefficient n-octanol/water (log value)</li> <li>Not determined.</li> <li>Vapour pressure at 20 °C:</li> <li>Density and/or relative density</li> <li>Density at 20 °C</li> <li>Relative density</li> <li>Vapour density</li> <li>Vapour density</li> <li>Vot determined.</li> <li>Vapour density</li> <li>Form:</li> <li>Fluid</li> </ul>	- Upper:	10.5 Vol % (64742-49-0 Hydrocarbons, C6, isoalkanes)
- Decomposition temperature:Not determined pHMixture is non-soluble (in water) Viscosity: Kinematic viscosityNot determined dynamic:Not determined Solubility Water:Not miscible or difficult to mix- Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined Partition coefficient n-octanol/water (log value) Density and/or relative density Density and/or relative density Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Form:Fluid	- Flash point:	10 °C
- Decomposition temperature:Not determined pHMixture is non-soluble (in water) Viscosity: Kinematic viscosityNot determined dynamic:Not determined Solubility Water:Not miscible or difficult to mix- Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined Partition coefficient n-octanol/water (log value) Density and/or relative density Density and/or relative density Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Form:Fluid	- Ignition temperature:	405 °C (64742-49-0 Hydrocarbons, C6, isoalkanes)
- Viscosity:       Not determined.         - Kinematic viscosity       Not determined.         - dynamic:       Not determined.         - Solubility       Not miscible or difficult to mix         - Water:       Not miscible or difficult to mix         - Partition coefficient n-octanol/water (log value)       Not determined.         - Vapour pressure at 20 °C:       3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)         - Density and/or relative density       0.73 g/cm³         - Relative density       Not determined.         - Vapour density       Not determined.         - Vapour density       Not determined.         - Jonsity at 20 °C       0.73 g/cm³         - Relative density       Not determined.         - Vapour density       Not determined.         - Vapour density       Not determined.         - Sourd density       Not determined.         - Form:       Fluid		Not determined.
Kinematic viscosityNot determined dynamic:Not determined SolubilityNot miscible or difficult to mix- Water:Not miscible or difficult to mix- Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density0.73 g/cm³- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined 9.2 Other information Appearance: Form:Fluid	-pH	Mixture is non-soluble (in water).
- dynamic:Not determined SolubilityNot miscible or difficult to mix- Water:Not miscible or difficult to mix- Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density0.73 g/cm³- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined 9.2 Other information Appearance: Form:Fluid	- Viscosity:	
- Solubility - Water: - Partition coefficient n-octanol/water (log value) - Vapour pressure at 20 °C: - Density and/or relative density - Density at 20 °C - Relative density - Relative density - Vapour density - Vapour density - Not determined. - Vapour density - 9.2 Other information - Appearance: - Form: - Form: - Form: - Not determined. - Pluid	- Kinematic viscosity	Not determined.
Water:Not miscible or difficult to mixPartition coefficient n-octanol/water (log value)Not determined.Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density0.73 g/cm³- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined 9.2 Other information Appearance:Fluid	- dynamic:	Not determined.
- Partition coefficient n-octanol/water (log value)Not determined Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density0.73 g/cm³- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined Vapour densityNot determined 9.2 Other information Appearance: Form:Fluid	- Solubility	
- Vapour pressure at 20 °C:3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)- Density and/or relative density0.73 g/cm³- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined 9.2 Other information Appearance:Fluid	- Water:	Not miscible or difficult to mix
- Density and/or relative density         - Density at 20 °C       0.73 g/cm³         - Relative density       Not determined.         - Vapour density       Not determined.         - 9.2 Other information       - Appearance:         - Form:       Fluid	- Partition coefficient n-octanol/water (log value)	Not determined.
- Density at 20 °C0.73 g/cm³- Relative densityNot determined Vapour densityNot determined 9.2 Other information Appearance:Fluid	- Vapour pressure at 20 °C:	3.1 hPa (64742-49-0 Hydrocarbons, C6, isoalkanes)
- Relative densityNot determined Vapour densityNot determined 9.2 Other information- Appearance:- Form:Fluid	- Density and/or relative density	
- Vapour densityNot determined 9.2 Other information - Appearance: - Form:Fluid	- Density at 20 °C	$0.73 \ g/cm^3$
- 9.2 Other information - Appearance: - Form: Fluid	- Relative density	Not determined.
- Appearance: - Form: Fluid	- Vapour density	Not determined.
- Form: Fluid	- 9.2 Other information	
	- Appearance:	
(Contd. on page 6)	- Form:	Fluid
		(Contd. on page 6)

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

Trade name: EXTREME BLACK

	(Contd. of page 5)
-Important information on protection of he	alth and
environment, and on safety.	
- Self-inflammability:	Product is not selfigniting.
- Explosive properties:	Product is not explosive. However, formation of explosive air/
	steam mixtures is possible.
- Change in condition	
- Evaporation rate	Not determined.
- Information with regard to physical hazard clas	ises
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Highly flammable liquid and vapour.
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flammable	e gases in
contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

**SECTION 10: Stability and reactivity** 

- 10.1 Reactivity Stable under normal conditions

- 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: Stable at ambient temperature

- 10.3 Possibility of hazardous reactions

Danger of containers bursting because of high vapour pressure Flammable

- 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: Flammable

- 10.6 Hazardous decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

-11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity

- LD/LC50 values that are relevant for classification:

64742-49-0 Hydrocarbons, C6, isoalkanes

*Oral LD50* >2,000 mg/Kg (Mouse)

Dermal LD50 >2,000 mg/Kg (Mouse)

# 63148-62-9 Poly (dimethylsiloxane)

Oral LD50 >15,400 mg/Kg (Rat)

Dermal LD50 >2,000 mg/Kg (Rabbit)

>2,000 mg/Kg (Rat)

(Contd. on page 7)

GB

Printing date 13.12.2022

Version number 3 (replaces version 2)

Revision: 13.12.2022

(Contd. of page 6)

#### Trade name: EXTREME BLACK

	120-51-4 Benzyl benzoate		
	Oral	LD50	>2,000 mg/Kg (Rat)
	Dermal	LD50	>2,000 mg/Kg (Rat) >2,000 mg/Kg (Rabbit) 4,000 mg/Kg (Rat)
			4,000 mg/Kg (Rat)
Skin correspondentiation Causes skin invitation			

- Skin corrosion/irritation Causes skin irritation.

STOT-single exposure May cause drowsiness or dizziness.
 Aspiration hazard May be fatal if swallowed and enters airways.

- 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

#### - 12.1 Toxicity

- Aquatic toxicity:

64742-49-0 Hydrocarbons, C6, isoalkanes

EC50 (72h) 55 mg/L (Algae)

63148-62-9 Poly (dimethylsiloxane)

*EC50 (48h)* >200 mg/L (Daphnia)

120-51-4 Benzyl benzoate

LC50 (96h) 2.32 mg/L (Fish)

*EC50 (48h)* 3.09 mg/L (Daphnia)

- -12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.

- 12.4 Mobility in soil No further relevant information available.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Toxic for fish
- Additional ecological information:

- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## **SECTION 13: Disposal considerations**

-13.1 Waste treatment methods

- Recommendation

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

GB

Printing date 13.12.2022

\*

Version number 3 (replaces version 2)

Revision: 13.12.2022

## Trade name: EXTREME BLACK

(Contd. of page 7)

SECTION 14: Transport informati	ion
- 14.1 UN number or ID number - ADR, IMDG, IATA	UN1268
- 14.2 UN proper shipping name - ADR	PETROLEUM DISTILLATES, N.O.S. (vapour pressure at 50°C no more than 110 kPa), ENVIRONMENTALLY HAZARDOUS
- IMDG - IATA	PETROLEUM DISTILLATES, N.O.S. (HEXANES), MARIN POLLUTANT PETROLEUM DISTILLATES, N.O.S.
	TETROLEOM DISTILLATES, N.O.S.
- 14.3 Transport hazard class(es)	
- ADR, IMDG	
- Class - Label - IATA	3 Flammable liquids. 3
- Class - Label	3 Flammable liquids. 3
- 14.4 Packing group - ADR, IMDG, IATA	11
- 14.5 Environmental hazards: - Marine pollutant:	Product contains environmentally hazardous substances: HEXANES Yes Symbol (fish and tree)
- Special marking (ADR):	Symbol (fish and tree)
- 14.6 Special precautions for user	Warning: Flammable liquids.
- Kemler Number:	33
- EMS Number: - Stowage Category	F-E,S-E B
14.7 Maritime transport in bulk according	
instruments	Not applicable.
Transport/Additional information: ADR	
- Limited quantities (LQ)	
- Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
- Tunnel restriction code - IMDG	D/E
- Limited quantities (LQ) Executed quantities (EQ)	1L Code: E2
- Excepted quantities (EQ)	Coae: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 50 ml

(Contd. on page 9)

GB

Version number 3 (replaces version 2)

Revision: 13.12.2022

#### Trade name: EXTREME BLACK

Printing date 13.12.2022


## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations
- Classification according to VbF: A I
- Technical instructions (air):

Class Share in %



- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

#### - Relevant phrases

H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. - Department issuing data specification sheet: Ma-Fra Laboratories - Contact: lab@mafra.it - Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 - \* Data compared to the previous version altered.

(Contd. of page 8)