

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** POWER WHEEL
- **UFI:** CMD0-C02R-600D-WWM8
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Life cycle stages** PW Widespread use by professional workers
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC35 Washing and cleaning products (including solvent based products)
- **Application of the substance / the mixture** Exterior vehicle cleaner
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MA-FRA S.p.A. a Socio Unico
Via Aquileia, 44/46
20021 Baranzate (MI) ITALIA
Tel. +39 023569981
www.mafra.com
mafra@mafra.it
- **Informing department:**
E-mail: lab@mafra.it
info@mafra.it
- **1.4 Emergency telephone number:** In case of accident call the emergency number 112

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labelling:**
sodium hydroxide
1-hydroxy ethylidene-1,1diphosphonic acid
- **Hazard statements**
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**
P102 Keep out of reach of children.
P260 Do not breathe mist/vapours/spray.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 1)

P280 Wear protective gloves / eye protection / face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with local/regional/national/international regulation

- 2.3 Other hazards**- Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures**- Description:** Mixture of substances**- Dangerous components:**

CAS: 64-02-8 EINECS: 200-573-9 Reg.nr.: 01-2119486762-27	tetrasodium ethylenediaminetetraacetate STOT RE 2, H373; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332	5-<10%
CAS: 78330-20-8 EC number: 616-607-4	Ethoxy Alcohol C9-C11 Eye Dam. 1, H318; Acute Tox. 4, H302	3-5%
CAS: 1310-73-2 EINECS: 215-185-5 Reg.nr.: 01-2119457892-27	sodium hydroxide Met. Corr. 1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318 Specific concentration limits: Skin Corr. 1A; H314: $C \geq 5\%$ Skin Corr. 1B; H314: $2\% \leq C < 5\%$ Skin Irrit. 2; H315: $0.5\% \leq C < 2\%$ Eye Irrit. 2; H319: $0.5\% \leq C < 2\%$	1-<3%
CAS: 2809-21-4 EINECS: 220-552-8 Reg.nr.: 01-2119510391-53	1-hydroxy ethylidene-1,1diphosphonic acid Met. Corr. 1, H290; Eye Dam. 1, H318; Acute Tox. 4, H302	1-<3%
CAS: 1310-58-3 EINECS: 215-181-3 Reg.nr.: 01-2119487136-33	potassium hydroxide Met. Corr. 1, H290; Skin Corr. 1A, H314; Acute Tox. 4, H302 Specific concentration limits: Skin Corr. 1A; H314: $C \geq 5\%$ Skin Corr. 1B; H314: $2\% \leq C < 5\%$ Skin Irrit. 2; H315: $0.5\% \leq C < 2\%$ Eye Irrit. 2; H319: $0.5\% \leq C < 2\%$	1-<3%
CAS: 68515-73-1 NLP: 500-220-1 Reg.nr.: 01-2119488530-36	Alkyl polyglucosyde C8-C10 Eye Dam. 1, H318	1-<3%

- Regulation (EC) No 648/2004

EDTA and salts thereof	$\geq 5 - < 15\%$
non-ionic surfactants, phosphonates, perfumes (Alpha Hexyl Cinnamaldehyde, LINALOOL, (R)-p-mentha-1,8-diene)	<5%

- Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures**- General information**

Instantly remove any clothing soiled by the product.

No special measures required.

- After inhalation

In case of unconsciousness bring patient into stable side position for transport.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 2)

*Supply fresh air; consult doctor in case of symptoms.***- After skin contact***Instantly wash with water and soap and rinse thoroughly.**If skin irritation continues, consult a doctor.***- After eye contact***Rinse opened eye for several minutes under running water. Then consult doctor.**Use eye protection.***- After swallowing***Drink copious amounts of water and provide fresh air. Instantly call for doctor.**Do not induce vomiting; instantly call for medical help.***- 4.2 Most important symptoms and effects, both acute and delayed***Sickness**No further relevant information available.***- Danger** *Danger of gastric perforation.***- 4.3 Indication of any immediate medical attention and special treatment needed***If swallowed, gastric irrigation**Medical supervision for at least 48 hours***SECTION 5: Firefighting measures****- 5.1 Extinguishing media****- Suitable extinguishing agents***CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.**Use fire fighting measures that suit the environment.***- 5.2 Special hazards arising from the substance or mixture***Can be released in case of fire**Carbon monoxide (CO)***- 5.3 Advice for firefighters****- Protective equipment:***Do not inhale explosion gases or combustion gases.**Protection means for respiratory tract***- Additional information***Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.***SECTION 6: Accidental release measures****- 6.1 Personal precautions, protective equipment and emergency procedures***Product forms slippery surface when combined with water.**Particular danger of slipping on leaked/spilled product.**Protective gloves. (EN 374)***- For non-emergency personnel***Ensure adequate ventilation**Keep away from ignition sources**Wear protective clothing.***- For emergency responders***Butyl rubber, BR**PVC gloves**Nitrile rubber, NBR***- 6.2 Environmental precautions:***Inform respective authorities in case product reaches water or sewage system.**Dilute with much water.**Do not allow to enter drainage system, surface or ground water.***- 6.3 Methods and material for containment and cleaning up:***Dilute with much water.**Ensure adequate ventilation.**Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Use neutralising agent.*

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 3)

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Store in cool, dry place in tightly closed containers.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke while working.

- Information about protection against explosions and fires: Protect from heat.**- 7.2 Conditions for safe storage, including any incompatibilities****- Storage****- Requirements to be met by storerooms and containers:** Store only in the original container.**- Information about storage in one common storage facility:** Do not store together with acids.**- Further information about storage conditions:** Keep container tightly sealed.**- Class according to regulation on inflammable liquids:** Void**- 7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters**- Components with limit values that require monitoring at the workplace:****1310-58-3 potassium hydroxide**WEL Short-term value: 2 mg/m³**- DNELs****64-02-8 tetrasodium ethylenediaminetetraacetate**

Oral	Systemic Long-term Effects	25 mg/Kg bw/day (Consumers)
Inhalative	Local long-term effects	1.5 mg/m ³ (Industrial Workers)
		0.6 mg/m ³ (Consumers)
	Local short-term effects	3 mg/m ³ (Industrial Workers)
		1.2 mg/m ³ (Consumers)
	Systemic long-term effects	1.5 mg/m ³ (Industrial Workers)
		0.6 mg/m ³ (Consumers)
	Systemic Short-term Effects	2.5 mg/m ³ (Industrial Workers)
		1.5 mg/m ³ (Consumers)

1310-73-2 sodium hydroxide

Inhalative	Local long-term effects	1 mg/m ³ (Industrial Workers)
		1 mg/m ³ (Consumers)
	Local short-term effects	1 mg/m ³ (Industrial Workers)
		1 mg/m ³ (Consumers)

2809-21-4 1-hydroxy ethylidene-1,1diphosphonic acid

Oral	Systemic Long-term Effects	13 mg/Kg bw/day (Consumers)
	Systemic short-term effects	13 mg/m ³ (Industrial Workers)
		6.5 mg/m ³ (Consumers)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 4)

<i>Dermal</i>	<i>Systemic long-term effects</i>	<i>13 mg/Kg bw/day (Industrial Workers)</i>
1310-58-3 <i>potassium hydroxide</i>		
<i>Inhalative</i>	<i>Local long-term effects</i>	<i>1 mg/m³ (Industrial Workers)</i>
		<i>1 mg/m³ (Consumers)</i>
	<i>Systemic long-term effects</i>	<i>1 mg/m³ (Industrial Workers)</i>
		<i>1 mg/m³ (Consumers)</i>
68515-73-1 <i>Alkyl polyglucosyde C8-C10</i>		
<i>Oral</i>	<i>Systemic Long-term Effects</i>	<i>35.7 mg/Kg bw/day (Consumers)</i>
<i>Dermal</i>	<i>Systemic long-term effects</i>	<i>595,000 mg/Kg bw/day (Industrial Workers)</i>
		<i>357,000 mg/Kg bw/day (Consumers)</i>
<i>Inhalative</i>	<i>Systemic long-term effects</i>	<i>420 mg/m³ (Industrial Workers)</i>
		<i>124 mg/m³ (Consumers)</i>

- PNECs**64-02-8 tetrasodium ethylenediaminetetraacetate**

PNEC STP	43 mg/L (STP)
Soil	0.72 mg/Kg (Soil)
Soft Water	2.2 mg/L (Water)
Sea water	0.22 mg/L (Water)
Occasional Emission	1.2 mg/L (Water)

2809-21-4 1-hydroxy ethylidene-1,1diphosphonic acid

PNEC STP	20 mg/L (STP)
Soil	96 mg/Kg (Soil)
Soft Water	0.136 mg/L (Water)
Sea water	0.0136 mg/L (Water)
Sediment (soft water)	59 mg/Kg (Soil)
Sediment (sea water)	5.9 mg/Kg (Soil)

68515-73-1 Alkyl polyglucosyde C8-C10

PNEC STP	560 mg/L (STP)
Soil	0.654 mg/Kg (Soil)
Soft Water	0.176 mg/L (Water)
Sea water	0.0176 mg/L (Water)
Sediment (soft water)	1.516 mg/Kg (Soil)
Sediment (sea water)	0.152 mg/Kg (Soil)

- Additional information: The lists that were valid during the compilation were used as basis.**- 8.2 Exposure controls****- Appropriate engineering controls** No further data; see item 7.**- Individual protection measures, such as personal protective equipment****- General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- Breathing equipment: Not required.**- Hand protection**

Protective gloves. (EN 374)

Alkaline resistant gloves

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Butyl rubber, BR

PVC gloves

Nitrile rubber, NBR

- Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 16523-1:2015: Level 3).

- Eye/face protection



Tightly sealed safety glasses.

- Body protection: Alkaline resistant protective clothing

- Environmental exposure controls Disposal must be made according to official regulations.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Physical state

Fluid

- Colour:

Dark yellow

- Odour:

Pleasant

- Odour threshold:

Not determined.

- Melting point/freezing point:

<0 °C

- Boiling point or initial boiling point and boiling range

>100 °C

- Flammability

Not applicable.

- Lower and upper explosion limit

- Lower:

Not determined.

- Upper:

Not determined.

- Flash point:

Not applicable

- Ignition temperature:

n.a

- Decomposition temperature:

Not determined.

- pH at 20 °C

>12

- Viscosity:

- Kinematic viscosity

Not determined.

- dynamic:

Not determined.

- Solubility

- Water:

Fully miscible

- Partition coefficient n-octanol/water (log value)

Not determined.

- Vapour pressure at 20 °C:

23 hPa

- Density and/or relative density

- Density at 20 °C

1.1 g/cm³

- Relative density

Not determined.

- Vapour density

Not determined.

- 9.2 Other information

- Appearance:

- Form:

Fluid

- Important information on protection of health and environment, and on safety.

- Self-flammability:

Product is not selfigniting.

- Explosive properties:

Product is not explosive.

- Change in condition

- Evaporation rate

Not determined.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 6)

- Information with regard to physical hazard classes	
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Void
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flammable gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity Stable under normal conditions
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Reacts with strong acids
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

- LD/LC50 values that are relevant for classification:

64-02-8 tetrasodium ethylenediaminetetraacetate

Oral	LD50	1,780 mg/Kg (Rat)
------	------	-------------------

78330-20-8 Ethoxy Alcohol C9-C11

Oral	LD50	300-2,000 mg/Kg (Rat)
------	------	-----------------------

1310-73-2 sodium hydroxide

Oral	LD50	2,000 mg/Kg (Rat)
------	------	-------------------

68515-73-1 Alkyl polyglucosyde C8-C10

Oral	LD50	>2,000 mg/Kg (Rat)
------	------	--------------------

Dermal	LD50	>2,000 mg/Kg (Rat)
--------	------	--------------------

- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- 11.2 Information on other hazards

- Endocrine disrupting properties

1222-05-5	Abbalide
-----------	----------

List II

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 7)

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

64-02-8 tetrasodium ethylenediaminetetraacetate

LC50 (96h) >100 mg/L (Fish)

EC50 (48h) 140 mg/L (Daphnia)

EC50 (72h) >100 mg/L (Algae)

78330-20-8 Ethoxy Alcohol C9-C11

LC50 (96h) >100 mg/L (Fish)

EC50 (48h) >100 mg/L (Daphnia)

EC50 (72h) >100 mg/L (Algae)

1310-73-2 sodium hydroxide

LC50 (96h) 45 mg/L (Fish)

EC50 (48h) 40.4 mg/L (Daphnia)

LC50 (48h) 189 mg/L (Fish)

2809-21-4 1-hydroxy ethylidene-1,1diphosphonic acid

LC50 (96h) 195 mg/L (Fish)

EC50 (48h) 527 mg/L (Daphnia)

EC50 (96h) 7.2 mg/L (Algae)

1310-58-3 potassium hydroxide

LC50 (96h) 80 mg/L (Fish)

68515-73-1 Alkyl polyglucosyde C8-C10

LC50 (96h) 126 mg/L (Fish)

EC50 (48h) >100 mg/L (Daphnia)

EC50 (72h) 27.22 mg/L (Algae)

- **12.2 Persistence and degradability** The contained surfactants are easily biodegradable

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into soil.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 8)

SECTION 13: Disposal considerations**- 13.1 Waste treatment methods****- Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:**- Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****- 14.1 UN number or ID number****- ADR, IMDG, IATA**

UN1719

- 14.2 UN proper shipping name**- ADR, IMDG, IATA**

CAUSTIC ALKALI LIQUID, N.O.S. (SODIUM HYDROXIDE, POTASSIUM HYDROXIDE)

- 14.3 Transport hazard class(es)**- ADR, IMDG, IATA****- Class**

8 Corrosive substances.

- Label

8

- 14.4 Packing group**- ADR, IMDG, IATA**

II

- 14.5 Environmental hazards:**- Marine pollutant:**

No

- 14.6 Special precautions for user

Warning: Corrosive substances.

- Kemler Number:

80

- EMS Number:

F-A,S-B

- Segregation groups

(SGG18) Alkalis

- Stowage Category

A

- Segregation Code

SG22 Stow "away from" ammonium salts

SG35 Stow "separated from" SGG1-acids

- 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

- Transport/Additional information:**- ADR****- Limited quantities (LQ)**

1L

- Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

- Transport category

2

- Tunnel restriction code

E

- IMDG**- Limited quantities (LQ)**

1L

- Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

GB

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 4 (replaces version 3)

Revision: 23.11.2022

Trade name: POWER WHEEL

(Contd. of page 9)

*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Classification according to VbF:** Void
- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- **Relevant phrases**
 - H290 May be corrosive to metals.
 - H302 Harmful if swallowed.
 - H314 Causes severe skin burns and eye damage.
 - H318 Causes serious eye damage.
 - H332 Harmful if inhaled.
 - H373 May cause damage to organs through prolonged or repeated exposure.
- **Department issuing data specification sheet:** Ma-Fra Laboratories
- **Contact:** lab@mafra.it
- **Abbreviations and acronyms:**
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)
 - DNEL: Derived No-Effect Level (UK REACH)
 - PNEC: Predicted No-Effect Concentration (UK REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Met. Corr. 1: Corrosive to metals – Category 1
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- *** Data compared to the previous version altered.**

GB