

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE OF THE COMPANY/ UNDERTAKING**

**1.1 Product Identifier**

Product name: Dynax-UB (aerosol)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses: Protectant

**1.3.Details of the supplier of the safety data sheet**

Company name and address:

Bilt Hamber Laboratories Radford Way,  
Billericay,  
Essex,  
CM12 0EG  
United Kingdom

Tel: 01277 658899

Email: sales@bilthamber.com

**1.4.Emergency telephone number**

01277 658899 (office hours only)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Physical hazards: Aerosol 1 - H222, H229  
Health hazards: Skin Irrit. 2 - H315 STOT SE 3 - H336  
Environmental hazards: Aquatic Chronic 2 - H411  
Classification (67/548/EEC or 1999/45/EC):  
F+; R12. Xi; R38. N; R51/53. R67  
Human health: Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.  
Environmental: The product contains a substance which is toxic to aquatic organisms.  
Physicochemical: Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

**2.2. Label elements**

Pictogram



**Hazard statements:**

Signal word: Danger

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing vapour/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Contains: HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS, NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

(Continue...)

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

**Supplementary precautionary statements**

- P264 Wash contaminated skin thoroughly after handling.
- P273 Avoid release to the environment.
- P321 Specific treatment (see medical advice on this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P391 Collect spillage.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with national regulations.

**2.3 Other hazards**

This product does not contain any substances classified as PBT or vPvB.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS CAS number: 64742-49-0 EC number: 927-510-4	30-60%
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	REACH registration number: 01-2119475515-33-XXXX

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE CAS number: 68476-85-7 EC number: 270-704-2	10-30%
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280	

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY CAS number: 64742-48-9 EC number: 919-857-5	10-30%
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	REACH registration number: 01-2119463258-33-XXXX

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: FIRST AID MEASURES**

**4.1. Description of first aid measures**

**General information:**

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.  
Get medical attention if any discomfort continues.

- Inhalation: Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
- Ingestion: Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
- Skin contact: Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
- Eye contact: Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
- Protection of first aiders: First aid personnel should wear appropriate protective equipment during any rescue.

(Continue...)

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

**4.2. Most important symptoms and effects, both acute and delayed**

**General information**

See Section 11 for additional information on health hazards.

**4.3. Indication of any immediate medical attention or special treatment needed**

Notes for the doctor: Treat symptomatically.

**SECTION 5: FIRE-FIGHTING MEASURES**

**5.1. Extinguishing media**

Extinguishing media: Foam, Carbon dioxide or dry powder.

**5.2. Special hazards arising from the substance or mixture**

Specific hazards: Containers can burst violently or explode when heated, due to excessive pressure build-up.

**5.3. Advice for fire-fighters**

Advice for fire-fighters: Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

**6.2. Environmental precautions**

Environmental precautions: Avoid discharge into drains.

**6.3. Methods and material for containment and cleaning up**

Methods for cleaning up: Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

**6.4. Reference to other sections**

Refer to other sections: For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1. Precautions for safe handling**

Handling requirements: Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene:

Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage precautions: Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

**7.3. Specific end use(s)**

Specific end use(s): The identified uses for this product are detailed in Section 1.2.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

Occupational exposure limits:

**PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

(Continue...)

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

**HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (CAS: 64742-49-0)**

**DNEL**

Consumer - Oral; Long term systemic effects: 149 mg/kg/day  
Consumer - Dermal; Long term systemic effects: 149 mg/kg/day  
Workers - Dermal; Long term systemic effects: 300 mg/kg/day  
Consumer - Inhalation; Long term systemic effects: 447 mg/m<sup>3</sup>  
Workers - Inhalation; Long term systemic effects: 2085 mg/m<sup>3</sup>

**8.2. Exposure controls**

Eye/face protection: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection: No specific requirements are anticipated under normal conditions of use.

Other skin and body protection: Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.

Respiratory protection: No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

<b>Appearance:</b>	Aerosol
<b>Colour:</b>	Dark Brown
<b>Odour:</b>	Solvent
<b>Odour threshold:</b>	No information available
<b>pH:</b>	No information available.
<b>Melting point:</b>	No information available.
<b>Initial boiling point and range:</b>	-41 (-41 TO 215)°C @
<b>Flash point:</b>	-40°C Closed cup.
<b>Evaporation rate:</b>	No information available.
<b>Evaporation factor:</b>	No information available.
<b>Flammability (solid, gas):</b>	No information available.
<b>Lower flammability/explosive limit:</b>	0.6 %
<b>Upper flammable/explosive limit:</b>	9.5 %
<b>Vapour pressure:</b>	No information available.
<b>Vapour density:</b>	No information available.
<b>Relative density:</b>	0.705
<b>Solubility(ies):</b>	Insoluble in water.
<b>Partition coefficient:</b>	No information available.
<b>Auto-ignition temperature:</b>	240°C
<b>Decomposition Temperature:</b>	No information available.
<b>Viscosity:</b>	No information available.
<b>Explosive properties:</b>	No information available.
<b>Oxidising properties:</b>	No information available.

**9.2. Other information**

Other information: None.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1. Reactivity**

No test data specifically related to reactivity available for this product or its ingredients.

**10.2. Chemical stability**

The product may not be stable under some conditions of storage or use.

**10.3. Possibility of hazardous reactions**

Possibility of hazardous reactions: None known.

**10.4. Conditions to avoid**

Conditions to avoid: Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

temperatures or direct sunlight.

**10.5. Incompatible materials**

Materials to avoid: None known.

**10.6. Hazardous decomposition products**

None at ambient temperatures.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

Inhalation: May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.  
Skin contact: Causes skin irritation.  
Eye contact: Vapour or spray in the eyes may cause irritation and smarting.  
Acute and chronic health hazards: No known chronic or acute health risks.  
Route of exposure: Inhalation Skin and/or eye contact.

**Toxicological information on ingredients.**

**HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS**

**Acute toxicity - oral**

Acute toxicity oral (LD<sub>50</sub> mg/kg): 5,001.0

Species: Rat

ATE oral (mg/kg): 5,001.0

**Acute toxicity - dermal**

Acute toxicity dermal (LD<sub>50</sub> mg/kg): 2,001.0

Specie: Rabbit

ATE dermal (mg/kg): 2,001.0

**NAPHTHA (PETROLEUM), HYDROTREATED HEAVY**

**Acute toxicity - oral**

Acute toxicity oral (LD<sub>50</sub> mg/kg): 5,001.0

Species: Rat

ATE oral (mg/kg): 5,001.0

**Acute toxicity - dermal**

Acute toxicity dermal (LD<sub>50</sub> mg/kg): 3,001.0

Species: Rabbit

ATE dermal (mg/kg): 3,001.0

**SECTION 12: ECOLOGICAL INFORMATION**

**12.1. Toxicity**

Ecological information on ingredients.

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Acute toxicity - fish NOEC, 1-10 mg/l, Fish

Acute toxicity - aquatic plants LOEC, : 10-100 mg/l, Algae

Acute toxicity - microorganisms LOEC, : 1-10 mg/l, Activated sludge

**12.2. Persistence and degradability**

Persistence and degradability: No data available.

**12.3. Bioaccumulative potential**

Partition coefficient: No information available.

**12.4. Mobility in soil**

Mobility: No data available

**12.5. Results of PBT and vPvB assessment**

This product does not contain any substances classified as PBT or vPvB.

**12.6. Other adverse effects**

Other adverse effects: None known.

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1. Waste treatment methods**

General information: Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Disposal methods: Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

Waste class:

**SECTION 14: TRANSPORT INFORMATION**

**14.1. UN number**

UN No. (ADR/RID) 1950  
UN No. (IMDG) 1950  
UN No. (ICAO) 1950  
UN No. (ADN) 1950

**14.2. UN proper shipping name**

Proper shipping name (ADR/RID) AEROSOLS, FLAMMABLE  
Proper shipping name (IMDG) AEROSOLS, FLAMMABLE  
Proper shipping name (ICAO) AEROSOLS, FLAMMABLE  
Proper shipping name (ADN) AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es)**

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class 2.1	

**14.4. Packing group**

Transport labels



Not applicable.

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant



**14.6. Special precautions for user**

Ems	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
Not applicable.

**SAFETY DATA SHEET**  
**DYNAX-UB (AEROSOL)**

Revision Number 2  
Compilation date: 01/12/15  
Revision date: 03/01/2018

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulations**

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

**EU legislation**

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).  
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).  
Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.

**15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out

**SECTION 16: OTHER INFORMATION**

**Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Legal disclaimer:**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.