

| TECHNICAL SPECIFICATIONS QRC | 7/900 | 9/1300 | 14/1350 |
|--------------------------------|-----------------------|-----------------------|-------------------------|
| Number of cups | 7 su due file | 9 su due file | 14 su 3 file |
| Brush's diameter | 250 mm | 250 mm | 250 mm |
| Number of segments for brush | 12/36 | 12/36 | 12/36 |
| Main motor | 1,5 kW | 2,2 kW | 4 kW |
| Inverter size | 1,5 kW | 2,2 kW | 4 kW |
| Rotation spees of brushes | 200/900 rpm | 200/900 rpm | 200/900 rpm |
| Lifting motor | 0,37 kW | 0,37 kW | 0,37 kW |
| Oscillation motor | 0,55 kW | 0,55 kW | 0,55 kW |
| Number of oscillations | 10-50 osc/min | 10-50 osc/min | 10-50 osc/min |
| Lenght of oscillation | 110 mm | 110 mm | 110 mm |
| Conveyor motor | 0,55 kW | 0,75 kW | 1,1 kW |
| Conveyor inverter | 0,55 kW | 0,75 kW | 1,1 kW |
| Conveyor speed | 2-12 m/min | 2-12 m/min | 2-12 m/min |
| Dust collection duct, diameter | 4x90 mm | 4x90 mm | 6x90 mm |
| Weight | 650 kW | 950 Kg | 1500 Kg |
| Dimensions | 1785 x 1590 x 1900 mm | 1785 x 1826 x 1900 mm | 2100 x 1826 x h 1900 mm |

The QRC machine can also be used for high gloss finishing with the PRO Power for polishing, thus obtaining a perfectly scratch free, glossy and brilliant panel.

It can also be used, by changing the abrasives, on the metal deburring and on the treatment of stone surfaces.



QRC

7/900•9/1300•14/1350

Oscillating cup brush sanding machine. Suitable for the finishing of panels, doors and mouldings in narrow spaces.



APPLICATIONS

- Wood: finishing of panels, doors and kitchen doors
- Metal: deburring double laser cutting
- Stone: finish of ceramic surface and outdoor tables

CHARACTERISTICS

- Double/triple row of staggered sanding cups, with the rotation speed controlled by inverter
- Side to side reciprocation of the sanding cups controlled by inverter
- Sanding cups with reverse direction, allow to be fitted with different grits of abrasive on both sides of the brush
- High power Vacuum belt for feeding and sealing of pieces

ADVANTAGES

- The bevel effect of the edges, combined with the action of the rotating brushes, is very effective
- Extremely easy and fast system to replace the sanding brushes, as Quickwood tradition
- Extremely compact machine, to be easily integrated into tight spaces of existing production lines
- Quality performance from a low priced machine

