

# SAFETY DATA SHEET

Revision Date 29-Jan-2020 Version 4

## 1. IDENTIFICATION

**Product identifier** 

Product Name GASKET SEALANT & DRESSING 5 GR

Other means of identification

Product Code 09974

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

# 2. HAZARDS IDENTIFICATION

# Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Flammable liquids	Category 3

# Label elements

#### **Emergency Overview**

#### Signal word Danger

Fatal if swallowed May cause an allergic skin reaction May cause cancer Flammable liquid and vapor



Appearance Black Physical state Liquid Odor Alcohol

# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use non-sparking tools

Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see .? on this label) Specific treatment (see .? on this label)

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam to extinguish.

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
TALC	14807-96-6	15 - 40
ROSIN	8050-09-7	3 - 7

2-PROPANOL	67-63-0	3 - 7
ETHANOL	64-17-5	1 - 5
TITANIUM DIOXIDE	13463-67-7	1 - 5
CARBON BLACK	1333-86-4	0.1 - 1

# 4. FIRST AID MEASURES

Description of first aid measures

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Flammable.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required. Remove all sources of ignition.

**Environmental precautions** 

**Environmental precautions** See section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Keep away from

heat/sparks/open flames/hot surfaces. - No smoking. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use

personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC	TWA: 2 mg/m³ particulate matter	(vacated) TWA: 2 mg/m³ respirable	
14807-96-6	containing no asbestos and <1%	dust <1% Crystalline silica,	TWA: 2 mg/m³ containing no
	crystalline silica, respirable	containing no Asbestos	Asbestos and <1% Quartz
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more;use Quartz limit	
ROSIN	-	(vacated) TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m³ Formaldehyde
8050-09-7		Formaldehyde	
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m <sup>3</sup>
		(vacated) TWA: 980 mg/m <sup>3</sup>	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m <sup>3</sup>
		(vacated) STEL: 1225 mg/m <sup>3</sup>	
ETHANOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		(vacated) TWA: 1900 mg/m <sup>3</sup>	
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7		(vacated) TWA: 10 mg/m³ total	TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine
		dust	TWA: 0.3 mg/m³ CIB 63 ultrafine,
			including engineered nanoscale
CARBON BLACK	TWA: 3 mg/m³ inhalable particulate		IDLH: 1750 mg/m <sup>3</sup>
1333-86-4	matter	(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
			TWA: 0.1 mg/m³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Butyl acetate = 1

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Black
Odor Alcohol

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available

Melting point / freezing point

Boiling point / boiling range
Flash point

No information available
No information available
82 °C / 180 °F
58 °C / 136 °F

Evaporation rate <1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 12.0% Lower flammability limit: 2.0%

Vapor pressure 33 mm Hg @ 68°F Vapor density No information available

Relative density 1.3

Water solubility Partially soluble

Solubility(ies) No information available No information available Partition coefficient No information available **Autoignition temperature Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 10.892

DensityNo information availableBulk densityNo information availableSADT (self-accelerating)No information available

decomposition temperature)

### 10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

**Hazardous Decomposition Products** 

Carbon oxides Aldehydes Carboxylic acids

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Inhalation** May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** May be fatal if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ROSIN 8050-09-7	= 7600 mg/kg (Rat) = 3000 mg/kg (Rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	= 72600 mg/m³ (Rat) 4 h
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

## Information on toxicological effects

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carolingen.			
Chemical Name	ACGIH	IARC	NTP	OSHA
TALC	-	Group 3	-	X
14807-96-6		-		
ETHANOL	A3	Group 1	Known	X
64-17-5		-		
TITANIUM DIOXIDE	-	Group 2B	-	X
13463-67-7		-		
CARBON BLACK	A3	Group 2B	-	X

1333-86-4

• Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage

• Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Blood, Central nervous system, Central Vascular System (CVS), Eyes, Liver, Lungs,

Reproductive System, Respiratory system, Skin, Thyroid.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 44 mg/kg
ATEmix (dermal) 25170 mg/kg
ATEmix (inhalation-dust/mist) 230.9 mg/l

#### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

0.0275 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

# **Mobility**

No information available.

Chemical Name	Partition coefficient
2-PROPANOL	0.05
67-63-0	
ETHANOL	-0.32
64-17-5	

### Other adverse effects

No information available

#### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001, U154 U161

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status

2-PROPANOL 67-63-0	Toxic Ignitable
ETHANOL	Toxic
64-17-5	Ignitable

## 14. TRANSPORT INFORMATION

DOT

**UN/ID No** 1866

Proper shipping name: (Epoxy resin), solution, Limited Quantity (LQ)

**Hazard Class** 3 **Subsidiary class** 6.1 **Packing Group** Ш **Emergency Response Guide** 127

Number

IATA

**UN/ID No** ID 8000

Proper shipping name: Consumer commodity

**Hazard Class** Subsidiary hazard class 6.1 **ERG Code** 9L

**IMDG** 

UN/ID No 1866

Proper shipping name: (Epoxy resin), solution, Limited Quantity (LQ)

**Hazard Class** 3 Subsidiary hazard class 6.1 **Packing Group** Ш **EmS-No** F-E, S-E

## 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies Does not comply **EINECS/ELINCS ENCS** Does not comply **IECSC** Complies Complies **KECL PICCS** Complies **AICS** Does not comply

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0

#### SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

## **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ETHANOL	Carcinogen
64-17-5	Developmental
TITANIUM DIOXIDE	*Carcinogen (airborne, unbound particles of respirable
13463-67-7	size)
METHANOL	Developmental
67-56-1	
CARBON BLACK	*Carcinogen (airborne, unbound particles of respirable
1333-86-4	size)
METHYL ISOBUTYL KETONE	Carcinogen
108-10-1	Developmental

- Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage
- Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage
- \*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
TALC	X	X	X
14807-96-6			
2-PROPANOL	X	X	X
67-63-0			
ETHANOL	Χ	X	X
64-17-5			
TITANIUM DIOXIDE	Χ	X	X
13463-67-7			
WATER	-	-	X
7732-18-5			
METHANOL	X	X	X
67-56-1			
CARBON BLACK	X	X	X
1333-86-4			
METHYL ISOBUTYL KETONE	X	X	X
108-10-1			

# U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### **WHMIS Hazard Class**

D2B - Toxic materials, B3 - Combustible liquid, D2A - Very toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0

HMIS Health hazards 2 Flammability 2 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 29-Jan-2020

#### **Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**