

1. Identification

Product identifier	Motor Medic Fuel System Cleaner	
Other means of identification		
SDS number	M2616	
Part No.	M2616	
Tariff code	3811.19.0000	
Recommended use	Gasoline Fuel Additive	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	RSC Chemical Solutions	
Address	600 Radiator Road Indian Trail, NC 28079 United States	
Telephone	Customer Service:	(704) 821-7643
	Technical:	(704) 684-1811
Website	www.rscbrands.com	
E-mail	Not available.	
Emergency phone number	Emergency Telephone:	(303) 623-5716
	Emergency Contact:	RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

4.78% of the mixture consists of component(s) of unknown acute oral toxicity. 5.88% of the mixture consists of component(s) of unknown acute inhalation toxicity. 84.63% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 84.63% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum Distillate Aliphatic		68476-34-6	80 - < 90
Solvent Naphtha (petroleum), Light Arom.		64742-95-6	3 - < 5
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
BENZENE,1-METHYLETHYL-		98-82-8	< 0.3
NAPHTHALENE		91-20-3	< 0.3
Other components below reportable levels			5 - < 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up	Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.
--	---

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
----------------------------------	--

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
---	--

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	PEL	245 mg/m3
NAPHTHALENE (CAS 91-20-3)	PEL	50 ppm 50 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
		10 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	TWA	50 ppm	
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
Petroleum Distillate Aliphatic (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and vapor.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
		25 ppm
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	TWA	245 mg/m3
		50 ppm
NAPHTHALENE (CAS 91-20-3)	STEL	75 mg/m3
		15 ppm
	TWA	50 mg/m3
		10 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

Petroleum Distillate Aliphatic (CAS 68476-34-6) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid. Clear.
Physical state	Liquid.
Form	Liquid.
Color	Dark red.
Odor	Diesel Fuel odor
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	136.0 °F (57.8 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	4.27 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.12 lbs/gal estimated
Explosive properties	Not explosive.
Flammability class	Combustible II estimated
Moisture	< 0.5 %
Oxidizing properties	Not oxidizing.
Percent volatile	0.31 % estimated
Specific gravity	0.85 estimated
VOC (Weight %)	0.31 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful if swallowed. Narcotic effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
LC50	Rat	> 2000 ppm, 48 Hours
Oral		
LD50	Rat	6 g/kg
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Acute		
Inhalation		
LC50	Mouse	2000 ppm, 7 Hours 24.7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	1400 mg/kg
NAPHTHALENE (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg
	Rat	> 20 g/kg
Oral		
LD50	Guinea pig	1200 mg/kg
	Rat	490 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE,1-METHYLETHYL- (CAS 98-82-8) 2B Possibly carcinogenic to humans.

NAPHTHALENE (CAS 91-20-3)

2B Possibly carcinogenic to humans.

Petroleum Distillate Aliphatic (CAS 68476-34-6)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 2.7 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (<i>Oncorhynchus gorbuscha</i>) 1.11 - 1.68 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE,1-METHYLETHYL-	3.66
NAPHTHALENE	3.3

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	Not available.
UN proper shipping name	Consumer commodity (Yes)
Transport hazard class(es)	
Class	ORM-D
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IATA

UN number	ID8000
UN proper shipping name	Consumer commodity
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1268
UN proper shipping name	Petroleum Products, n.o.s. (Petroleum Distillate Aliphatic)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

IATA



IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Listed.

NAPHTHALENE (CAS 91-20-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 - < 3
NAPHTHALENE	91-20-3	< 0.3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
NAPHTHALENE (CAS 91-20-3)
Petroleum Distillate Aliphatic (CAS 68476-34-6)
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
NAPHTHALENE (CAS 91-20-3)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
NAPHTHALENE (CAS 91-20-3)
Petroleum Distillate Aliphatic (CAS 68476-34-6)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
NAPHTHALENE (CAS 91-20-3)
Petroleum Distillate Aliphatic (CAS 68476-34-6)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE,1-METHYLETHYL- (CAS 98-82-8)	Listed: April 6, 2010
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-10-2015
Revision date	06-11-2015
Version #	03

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Physical & Chemical Properties: Multiple Properties
Stability and reactivity: Possibility of hazardous reactions
Transport information: General information
Regulatory information: US federal regulations
GHS: Classification