

PRODUCT INFORMATION



ELECTRONIC CLEANER

CODE: NM4

PAGE: 1 of 1

DATE: June 2008

FUNCTION AND APPLICATION: Solder Seal®/Gunk® Electronic Cleaner is formulated for use on sensitive electronic components and plastics. Penetrates hard to reach areas to safely dissolve dirt, dust, grease, flux, and other contaminants. Evaporates quickly and completely. Regular use helps prevent contact malfunction and failure. Harmless to most plastics and paper tapes.

OUTSTANDING PROPERTIES: Solder Seal®/Gunk® Electronic Cleaner is safe for use on printed circuit boards. Perfect for cleaning shop electrical equipment. Regular use helps prevent contact malfunction and failure. Electronic Cleaner is non-conductive and contains no chlorinated solvents.

USE DIRECTIONS: Read entire label before using the product. 1) Do not apply to energized equipment. 2) Ensure adequate ventilation in the work area. 3) Spray small amount on the area to be cleaned. Swabs or lint-free cloths may be used. 4) Allow to dry completely and vent thoroughly before reactivating equipment. Product liquid or vapor may collect or pool in unseen areas. Be certain no flammable vapors remain before reactivation. 5) This product will remove lubrication from moving parts. Re-lubrication may be necessary.

DANGER: Contains (CAS#) hexane (110-54-3), petroleum distillates (64742-48-9), and carbon dioxide (CAS# 124-38-9). Extremely flammable, Harmful or fatal if swallowed, Vapor harmful, Contents under pressure. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. If inhaled, move to fresh air immediately. If breathing becomes difficult, get prompt medical attention. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. For additional information, consult the Material Safety Data Sheet. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects, and other reproductive harm.

STORAGE & HANDLING: Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or any heat source. This product is extremely flammable, do not apply while equipment is energized. Keep from flames and ignition sources including pilot lights. Do not smoke while using this product. Use only in a well ventilated area. Avoid continuous breathing of vapor or spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, headaches, dizziness, drowsiness, unconsciousness or death. Deliberate misuse by concentrating and inhaling vapors or swallowing product can be harmful or fatal. Vapors are heavier than air and will collect in low areas. Keep away from children and animals.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: Packaged in 4.5 weight oz. aerosol container.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.