

BRK KARTS DRIVE

SETUP SHEET



WET SLIPPERY TRACK

DRY GRIPPY TRACK

FRONT BAR	Loose	Firm
SIDE POD BARS	Loose	Firm
REAR BAR/FLOORTRAY	Loose	Firm
FRONT END ALIGNMENT	Neutral camber, 2mm toe out per side	Neutral camber, 2mm toe out per side
FRONT END WIDTH	1x 14mm & 1x 7mm spacer inside the wheel	1x 14mm spacer inside the wheel
RIDE HEIGHT	2 spacers at top, 1 at bottom	2 spacers at top, 1 at bottom
REAR HUBS - 7 INCH RIM	140mm - 145mm from chassis to face of hub	150mm - 155mm from chassis to face of hub
REAR HUBS - 8 INCH RIM	125mm from chassis to face of hub	135mm from chassis to face of hub



DRIVER UNDER 80KG:

DRIVER OVER 80KG:

TYRE PRESSURES	6-8 PSI all around	8-10 PSI all around
AXLE	Thin wall Axle	Thick wall Axle



SEAT POSITIONING: (GUIDE ONLY)

	150-160CM	160-170CM	170-180CM	180CM PLUS
DRIVER HEIGHT	150-160CM	160-170CM	170-180CM	180CM PLUS
PICTURE A	640MM	650MM	650MM	660MM
PICTURE B	730MM	740MM	750MM	765MM
BOTTOM OF SEAT	Flush with top of chassis	Middle of Chassis	Middle of Chassis	Flush with top of chassis

PIC (A) - FRONT OF CHASSIS TO FRONT EDGE OF SEAT

PIC (B) - TOP OF PLASTIC STEERING BLOCK TO BACK EDGE OF SEAT

