

Vektor3600-AC

Whole-home mesh wireless system

AEFME904U1

Professional Series



Modular system with 3 nodes



Full-speed Wi-Fi up to 4,000 SQ FT



Guest access & parental control



5-year warranty must register at: nexxtsolutions.com/warranty



Parental Control

True Mesh







One network name and password



Smartphone setup



NEXXT Wireless Mobile application


One seamless network that covers every inch of your home

Product overview

Update your wireless connection to the next generation of modular Wi-Fi mesh systems introduced by NEXXT Solutions®. This scalable solution ensures an extra 1500ft of reliable signal transmission with each node that is added, far beyond the reach of any standard router or extender. It extends the coverage of your network by effectively reducing dead zones with an ultra-fast, reliable and secure wireless signal.

Highlights

- · Whole-home communication network that supports up to 30 devices connected simultaneously
- True Mesh technology, a more efficient approach to wireless networks
- AC3600 combined speeds.1200Mbps per node (300Mbps at 2.4GHz/ 867Mbps at 5.0GHz)
- Easy Setup through the NEXXT Wireless mobile application
- NEXXT Cloud feature for live status and remote management
- Eliminates dead spots and weak signals
- · Manage just one network name and password for all nodes
- Intelligently chooses the shortest and fastest route
- · Guest access for segmented networks
- Parental control settings
- Bandwidth control prioritizes traffic for bandwidth intense applications









Vektor3600-AC

Whole-home mesh wireless system

AEFME904U1

Professional Series

Technical specifications

	Vektor3600-AC
Hardware features	
Number of nodes	3
Standards	IEEE802.3, IEEE802.3u, IEEE802.11V/R
Protocols	DHCP Server, DNS, Port forwarding
Ports and interface	1 x 10/100Mbps WAN/LAN
	1 x 10/100Mbps LAN
Antennas	2 x Internal 3dbi omnidirectional per node
Button	Reset
LED indicators	System/Power
Wireless features	
Standards	IEEE 802.11ac/a/n 5GHz
	IEEE 802.11 b/g/n 2.4GHz
Frequency band	2.4GHz and 5GHz
Wireless rate	2.4GHz: 300Mbps + 5.0GHz: 867Mbps
Radio data rate	IEEE 802.11ac: up to 867Mbps
	IEEE 802.11n: up to 300Mbps
	IEEE 802.11g: up to 54Mbps
	IEEE 802.11b: up to 11Mbps
Channels	2.4G :1-13
	2.4G .1-13 5G: 36-161

Channel width	20MHz / 40MHz / 80MHz
Security	WPA-PSK/WPA2-PSK
Working mode	Wireless router, AP, Bridge
Wireless function	Wireless security: enable/disable
	Transmission power control
	Fast roaming: enable/disable
	Bandwidth control
	Wireless schedule
	Guest network
	Parental control groups
	Mobile application
	Port forwarding
	Automatic node detection
	Beamforming technology
Software features	Bearmonting tearnology
Internet connection type	Dynamic IP, PPPoE, Static IP, bridge mode
DHCP	DHCP Server, DHCP Client
Security	Parental Control, Firewall, Remote Management
Firewall	Forbid UDP flood attack, TCP flood attack, ICMP attack
Virtual server	Port Forwarding, UPnP
Other advanced function	Guest Network, Online Firmware Update, QOS, Maintenance Schedule
Environment	
Operating temperature	32°F-104°F
Storage temperature	-40°F -158°F
Relative humidity	Operating humidity: 10%-90% non-condensing
	Storage humidity: 5%-90% non-condensing
Physical characteristics	
Housing	ABS plastic
Color	White
	3.5x3.5x3.5in (90x90x90mm) per node
Product dimensions	0.6lb (0.25kg) per node
Product weight	o.oib (o.25kg) per node
Additional information	0.000
Power	9V/1A
Warranty	5 years*
Certificates	FCC
Included	3 wireless mesh nodes
	3 power adapters
I I	
	Ethernet cable

^{*2-}year standard warranty plus a 3-year extension with online registration