

Contourz [kon-toors]

A specially designed mix of engineering and artistry deliver Contourz concrete tiles in serene colors and modern shapes with three-dimensional or flat surfaces. With a similar thickness to many of LBT's ceramic and glass series, design possibilities are broadened even further. Custom colors are also available.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2020 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application	Suitable			Interior	Exterior
Interior Wall/Backsplash	Yes		Shower	No	No
Fireplace/Cooktop Surround	Yes *		Steam Shower	No	N/A
Shower Wall	Yes		Light Residential	Yes	No
Steam Shower	No		Residential	No	No
Exterior Wall	Yes				
Pool, Spa or Water Feature (fully submerged)	No				
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Piece)	Packaging (Per Box)	Standards Methods		
3 x 9"	5.71	15 Pieces/2.627 SF	Breaking Strength	ASTM C-648	>16000 PSI
4" Hex	10.95	52 Pieces/4.749 SF	Water Absorption	ASTM C-373	Vitreous ≥ .05% - ≤ 3.0%
6 x 9"	2.82	15 Pieces/5.319 SF	Chemical Resistance	ASTM C-650	Pass
Fanfare Hex (4")	10.95	28 Pieces/2.557 SF	Freeze/Thaw	ASTM C-1026	Unaffected
In & Out (2 ½ x 9")		12 Pieces/Box	Warpage	ASTM C-485	± 0.26%/± 1.5mm
Retro Curve (1 ½ x 9")		18 Pieces/Box	NOTES Since variations are common in artistic concrete tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used due to the luster glaze. please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed). Contourz has similar characteristics and care requirements as natural stone (marble or limestone).		
Trifecta (9 x 10 ¼")	3.15	6 Pieces/1.905 SF			
Zen Break A (3 x 9")	5.71	16 Pieces/2.802 SF			
Zen Break B (3 x 9")	5.71	16 Pieces/2.802 SF			
Shade Variation	Grout Joint Recommendation		MAINTENANCE A routine cleaning of Contourz tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.		
V2 - Slight Variation	1/8" (3 mm)				

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. Not recommended for placement inside a firebox.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.