Introducing Jonathan Adler's debut tile series with Lunada Bay Tile—Shelter Island. Inspired by the tones of the land, sea, and air surrounding Jonathan's iconic home, these quiet, semi-matte hues are harmonious with both minimalist and maximalist spaces. Finished with semi-transparent glazes that accentuate the handcrafted textures and dimension beneath, adding subtle depth to your abode.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.



© 2022 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	No	No
Fireplace/Cooktop Surround	Yes *	Steam Shower	No	N/A
Shower Wall	Yes	Light Residential	Yes ▲	No
Steam Shower	Yes **	Residential	No	No
Exterior Wall	Yes			
Pool, Spa or Water Feature (fully submerged)	No			

PRODUCT SPECS		TESTING			
Size (Dimension In Nominal Size)	Coverage (Pieces per SF)	Packaging (Per Box)			
4 ¾ x 9 ½ Field	3.212	16 Pieces / 4.981 SF	Breaking Strength	ASTM C-648	> 450 PSI
Arc (4 ¾ x 4 ¾")	6.452	32 Pieces / 4.96 SF	Water Absorption	ASTM C-373	Vitreous ≥ 0.5% -≤ 3.0%
Facet (4 ½ x 4 ½")	6.452	32 Pieces / 4.96 SF	Chemical Resistance	ASTM C-650	Unaffected
Linocut (4 ¾ x 9 ½")	3.212	16 Pieces / 4.981 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Orbit (4 ½ x 4 ½")	6.452	32 Pieces / 4.96 SF	Warpage	ASTM C-485	± 0.26% / ± 1.5 mm
Quadrant (4 ¾ x 4 ¾")	6.452	32 Pieces / 4.96 SF			
Liner (% x 9 %")		80 Pieces		NOTES	

r (¾ x 9 ½")	80 Pieces		
Shade Variation	Grout Joint Recommendation		
V1 - V2 Slight Variation	1/8" (3 mm)		

NOTES

Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of **Shelter Island** can be done with light duty, diluted close to neutral pH cleaner.

- Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/ cooktop surround. NOT recommended for placement inside a firebox.
- ** Aged Bronze finish is not recommended for installation in steam showers due to metallic glaze.
- ▲ Linocut and 4 ¾ x 9 ½ Field ONLY. All other patterns are NOT recommended for use on floors.

Floor Application Definitions:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.