


DIP TANK INSTRUCTIONS

USING EASISTRIP SUPRA ONE STEP INK CLEANER & EMULSION REMOVER



1. SCRAPE INK



2. PULL TAPE



3. DIP SCREENS

(1-3 MINS OR UNTIL FILM LOOSENS FROM MESH)



4. PRESSURE RINSE




**5. SPRAY EASIWAY
STAIN REMOVER**



6. SCRUB



7. PRESSURE RINSE



8. FLOOD RINSE

After your Easiway Dip Tank is set up and filled with Easiway Ink and Emulsion remover, follow the steps to begin reclaiming your screens. Should you have any questions, concerns, or need to reorder, please contact us!

STEP 1: ASSEMBLY

Find the white, plastic on-off spigot included with your tank set up (this piece will be included with all dip tanks except for PT-506 tanks). This should be sealed in a plastic bag and attached to the inner wall of your tank.

STEP 2: FILLING THE TANK

Turn the tank on its side and insert the threaded end of the spigot into the female receptacle located on the bottom end of the tank.

Be careful to NOT OVER TIGHTEN. Usually 2 or 3 rotations of the spigot are all that is necessary to seal the threads. If the spigot is over tightened, the spin fitting will crack, causing the tank to leak. When this is completed, turn the tank upright and move it to the location where it will be situated. Generally, you would place the tank within close proximity of the washout booth where the screens will be rinsed.

TANK	VOLUME	DIMENSIONS	RATIO	CHEMICAL	WATER
PT-506	14 Gallons 53 Liters	24"W x 4.5"D x 30"H	1:7	2 Gallons	Up to 12 Gallons
PT-525	25 Gallons 95 Liters	37"W x 13"D x 28"H	1:7	4 Gallons	Up to 21 Gallons
PT-520	37 Gallons 140 Liters	30"W x 8"D x 36"H	1:7	5 Gallons	Up to 32 Gallons
PT-598	84 Gallons 318 Liters	36"W x 18"D x 30"H	1:7	12 Gallons	Up to 72 Gallons
PT-579	105 Gallons 397 Liters	40"W x 16"D x 38"H	1:7	15 Gallons	Up to 90 Gallons

STEP 3: RECLAIMING SCREENS

After your Dip Tank is set up and filled with Easiway Ink & Emulsion remover, submerge your screen in the solution, allow it to soak briefly, then rinse thoroughly with a pressure washer to remove ink, emulsion, and stains in one easy step. After finishing the final flood rinse your screen is reclaimed. There is no need to further degrease your screens.