

# EASISOLV 1028

## INK CLEANER & EMULSION REMOVER

EasiSolv™ 1028 Ink & Emulsion Remover is a ready-to-use liquid cleaner that provides a revolutionary, streamlined approach to cleaning and reclaiming UV and plastisol printing screens. When used as directed, this unique product dissolves ink, water-soluble screen block out, direct emulsion, capillary film as well as tape adhesive residue. EasiSolv 1028 is a low-odor, non-flammable, biodegradable, non-hazardous product that will provide the benefits of less labor, less expense, and improved efficiency to the screen cleaning and reclaiming operation.

<b>Appearance:</b>	Clear, light yellow
<b>Odor:</b>	Citrus
<b>Ph:</b>	Neutral
<b>Flash Point:</b>	>93°C / 200°F
<b>Specific Gravity:</b>	0.95 @ 20°C / 68°F
<b>Weight/gl:</b>	6.4 lbs/gallon
<b>VOCs:</b>	950 grams/liter
<b>Dot Shipping:</b>	Non-hazardous

<b>Quart</b>	
<b>Gallon</b>	1028-1 GL
<b>5 Gallon pail</b>	1028-5 GL
<b>55 Gallon Drum</b>	1028-55 GL

### STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as caustics.

### PRODUCT FEATURES

- Alternative to SUPRA for UV/Solvent, Conductive, and Industrial Inks
- For use in a dip tank
- Zero VOCs Non-flammable
- Non-hazardous

### APPLICATION/USE

Scrape excess ink from screen. Wet both sides of screen with water. Apply EasiSolv 1028 by brush, wipe, scrub pad or spray to the print side of screen and scrub. Apply to the ink (well) side of screen and scrub. High pressure rinse from the well side followed by high pressure rinse from the print side, giving good attention to the image area and frame. Flood rinse entire screen with low pressure water. If stubborn stains remain, apply an Easiway approved stain remover and high pressure rinse.

### COMPATIBLE INK TYPES

- Plastisol
- Waterbased
- UV-Solvent
- Conductive
- Industrial