

EASISOLV 35

LOW FOAM SCREEN WASH & STAIN REMOVER

EasiSolv 35 Screen Wash & Stain Remover is designed to dissolve plastisol and UV inks from the screen printing mesh before removing the emulsion. This product is applied to the screen printing mesh and rinsed with water. It also contains surfactants that degrease the screen printing mesh when used as a final step in the reclaiming process. C35 is an Easiway approved stain remover, dissolving ink stains, emulsion residue, and ghost images from the screen printing mesh. This product has less than 100 grams per liter VOC content.

Appearance:	Colorless to slight yellow
Odor:	Solvent
Ph:	Not Applicable
Flash Point:	93°C / > 200°F
Specific Gravity:	1.151 gm/cc @ 20°C/68°F
Weight/gl:	Not Determined
VOCs:	99 grams/liter
Dot Shipping:	Non-hazardous

Quart	
Gallon	35-1 GL
5 Gallon pail	35-5 GL
55 Gallon Drum	35-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents.

PRODUCT FEATURES

- Fast ink dissolution for efficient cleaning
- Simultaneous degreasing simplifies process
- Low odor enhances workplace environment
- Biodegradable detergents with low foam ensure superior ink removal
- Versatile application methods for optimal performance and longevity

APPLICATION/USE

Scrape excess ink from the screen, apply EasiSolv 680 to the ink side and print side of the screen and scrub. Using a good high pressure washer, spray rinse the screen starting at the bottom on the ink side and work up. Give good attention to the image area. Rinse the print side of the screen. Apply an Easiway emulsion remover. If stubborn stains remain, apply EasiSolv 601 as a stain remover.

COMPATIBLE INK TYPES

- Plastisol
- Waterbased
- UV/Solvent
- Conductive
- Industrial